## ATGBICS WSP-Q40GLR4L Cisco Compatible Transceiver QSFP+ 40GBase-IR4 (1310nm, SMF, 2km, DOM)

Brand : ATGBICS

Product code: WSP-Q40GLR4L-C

Product name : WSP-Q40GLR4L Cisco Compatible Transceiver QSFP+ 40GBase-IR4 (1310nm, SMF, 2km, DOM)

WSP-Q40GLR4L Cisco Compatible Transceiver QSFP+ 40GBase-IR4 (1310nm, SMF, 2km, DOM)


ATGBICS WSP-Q40GLR4L Cisco Compatible Transceiver QSFP+ 40GBase-IR4 (1310nm, SMF, 2km, DOM):

ATGBICS WSP-Q40GLR4L 40GBase-IR4 supports a distance of up to 2km over multi mode fibre (SMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of WSP-Q40GLR4L= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *40000 Mbit/sInterface type *QSFP+Single-mode fiber (SMF) supportedMulti-mode fiber (MMF) supportedFiber optic connectorLCSFP transceiver standardIR4Maximum transfer distance2000 mWavelength1310 nmEthernet LANEthernet interface type40 Gigabit EthernetDigital Diagnostics Monitoring (DDM)Wavelength	40000 Mbit/s QSFP+ ✓	Certification	CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 3.5 W
		Operational conditions Maximum operating temperature	70 °C
	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 70 °C -40 - 85 °C 0 - 95%	
	-	Storage relative humidity (H-H) Weight & dimensions	0 - 95%
Wavelength-division multiplexing (WDM)	×	Width	13.5 mm 72.4 mm
FeaturesProduct colourSilverHousing materialMetalPlug and PlayImage: Image: Imag		Depth Height Weight	18.4 mm 42 g
	√	Packaging data	
	4	Number of products included Package type	1 pc(s) Box
Easy to install Country of origin	✓ United Kingdom	Technical details	
Brand compatibility	Cisco	Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468716507

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.