
PRODUCT DATASHEET CP16632_CARMEN-50-RS-C-WHT

CARMEN-50-RS-C-WHT

~11° spot beam. Assembly with holder C compatible with LEDiL HEKLA. White version.

SPECIFICATION:

Dimensions	Ø 50.0 mm
Height	25.5 mm
Fastening	socket
ROHS compliant	yes 🕕



MATERIALS:

Component	Type	Material	Colour	Finish
CARMEN-50-RS	Single lens	PMMA	clear	
CARMEN-50-HI D-C-WHT	Holder	PC	white	


ORDERING INFORMATION:

» Box size: 476 x 273 x 292 mm

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP16632_CARMEN-50-RS-C-WHT	Single lens	308	112	28	7.2




PRODUCT DATASHEET CP16632_CARMEN-50-RS-C-WHT




See also our general installation guide: www.ledil.com/installation_guide







PRODUCT DATASHEET CP16632_CARMEN-50-RS-C-WHT



PRODUCT DATASHEET CP16632_CARMEN-50-RS-C-WHT







PRODUCT DATASHEET CP16632_CARMEN-50-RS-C-WHT


OPTICAL RESULTS (SIMULATED):

CITIZEN

LED CLL02x/CLU02x (LES10)

FWHM / FWTM 15.0° / 30.0°
Efficiency 87 %
Peak intensity 6.6 cd/lm
LEDs/each optic 1
Light colour White

Required components: F15255_HEKLA-SOCKET-C



CREE + LED

 LED
 CMU15xx


 FWHM / FWTM
 27.0° / 56.0°

 Efficiency
 91 %

 Peak intensity
 2.6 cd/lm

Peak intensity 2.6 cd LEDs/each optic 1 Light colour White

Required components: F17438_HEKLA-G2-I



CREE = LED


 LED
 CMU15xx

 FWHM / FWTM
 26.0° / 54.0°

 Efficiency
 91 %

Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17438_HEKLA-G2-I




MUMILEDS

LED LUXEON CoB 1202/1203

FWHM / FWTM 16.0° / 30.0°
Efficiency 88 %
Peak intensity 6.5 cd/lm
LEDs/each optic 1
Light colour White


F15858_HEKLA-SOCKET-H

Required components:





OPTICAL RESULTS (SIMULATED):





PRODUCT DATASHEET CP16632 CARMEN-50-RS-C-WHT

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy