



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00605	Connector, 4 pin M5 socket, 5xL14.5mm, gold plated, molding style, solder cup, IP67	1	
2	30-00495	Wire, 3C TS, 28 AWG, 150V, 70C, 2.8 mm, spiral shield, TPU, WBL	1	original component only
3	24-00263	Overmold, M5, 6xL22 mm	1	TPU, black
4	Heat shrink	black	1	covers stripped wire end
5	Heat shrink	black	1	covers shield



Front View
Not to Scale

Notes:
Functionally equivalent components may be substituted

IP67 waterproof rating when mated with corresponding (IP67) connector

Cable rated for 60 V, 1.0 A

Wiring Diagram	
50-00605	wire color
1	red
2	white
3	black
4	shield

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	09/14/2018	Initial release	JC <small>Digitally signed by JC Date: 2020.03.20 08:42:16 -07'00'</small>		
			Verified:	Function test: no open, no short circuit, no intermittent	Size: Part number:
			AG <small>Digitally signed by AG Date: 2020.03.20 09:57:23 -07'00'</small>	Description:	A 10-03015
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, 5x0.5 mm 4C 50-00605 M5 socket to 5 mm tinned, 28 AWG, 30-00495 wire, IP67	Scale: 1:1
					Sheet 1 of 1

5

4

3

2

1