

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

# **DRAM Click**





#### PID: MIKROE-5337

**DRAM Click** is a compact add-on board representing a dynamic random-access memory solution. This board contains the <u>APS6404L-3SKR</u> from <u>AP Memory</u>, a high-performance 64Mb SPI/KPI PSRAM memory organized as 8M x 8 bits each. This Pseudo-SRAM device features a high speed, low pin count interface and incorporates a seamless self-managed refresh mechanism to maximize the performance of memory read operation. It has 4 SDR I/O pins and operates in SPI or QPI (quad peripheral interface) mode with frequencies up to 133 MHz. This Click board<sup>™</sup> is most suitable for low-power and low-cost portable applications.

DRAM Click is supported by a <u>mikroSDK</u> compliant library, which includes functions that simplify software development. This <u>Click board</u><sup>TM</sup> comes as a fully tested product, ready to be used on a system equipped with the <u>mikroBUS</u><sup>TM</sup> socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

## Specifications

Туре	DRAM
Applications	Can be used for low-power and low-cost portable applications
On-board modules	APS6404L-3SQR - 64Mb PSRAM (Pseudo-SRAM) memory from AP Memory
Key Features	Low power consumption, SPI/QPI with SDR mode, high performance, organized as 8M x 8bits, page size of 1024 bytes, self-managed refresh mechanism, software reset, and more
Interface	QSPI,SPI
ClickID	No
Compatibility	mikroBUS
Click board size	S (28.6 x 25.4 mm)
Input Voltage	3.3V

### Resources

<u>mikroBUS</u>™

<u>mikroSDK</u>

Click board<sup>™</sup> Catalog

Click Boards<sup>™</sup>

### **Downloads**

DRAM click example on Libstock

DRAM click 2D and 3D files

APS6404L-3SQR datasheet

DRAM click schematic

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).