

# DA PowerCool Series, DA-024-24-02 Thermoelectric Assembly

### Innovative **Technology** for a **Connected** World



### **POWERCOOL SERIES DIRECT-TO-AIR THERMOELECTRIC ASSEMBLY**

The DA PowerCool Series is a Direct-to-Air thermoelectric assembly (TEA) that uses impingement flow to transfer heat. It offers dependable, compact performance by cooling objects via conduction. Heat is absorbed through a cold plate and dissipated thru a high density heat exchanger equipped with an air ducted shroud and brand name fan. The thermoelectric modules are custom designed to achieve a high coefficient of performance (COP) to minimize power consumption. This product series is available in a wide range of cooling capacities and voltages. Custom configurations and moisture protection options are available, however, MOQ applies.

#### FEATURES **Rolls**


- Compact design
- Precise temperature control
- Reliable solid-state operation
- DC operation
- RoHS compliant

### **APPLICATIONS**

- Analytical instrumentation
- Medical diagnostics
- Photonics laser systems
- Industrial instrumentation
- Food and beverage cooling

Specifications	
Cooling Power Qcmax (W)	24
Running Current (A)	2.0
Startup Current (A)	2.8
Nominal Voltage (V)	24
Max Voltage (V)	30
Power Input (W)	48
Operating Temperature (°C)	-10 to 48
Weight (kg)	0.3
MTBF (fans – hrs)	50,000
Performance Tolerance	±10%

# **PERFORMANCE CURVE**



## global solutions: local support...

Americas: +1.888.246.9050 Europe: +46.31.704.67.57 Asia: +86.755.2714.1166


CLV-customerservice@lairdtech.com www.lairdtech.com/thermal




# DA PowerCool Series, DA-024-24-02 Thermoelectric Assembly

Innovative **Technology** for a **Connected** World


### **ISOMETRIC DRAWINGS**






### **MOUNTING HOLE LOCATION**

### **WIRING SCHEMATIC**





### **NOTES**

For indoor use only. Thermally conductive grease enclosed.

#### THR-DS-DA-024-24-02 0310

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no waranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from the to time, a copy of which will be furnished upon request. © Copyright 2010 Laird Technologies, ne. All Rights Reserved. Laird Technologies, the Laird Technologies Laird, and so are subjected to advant of the Laird Technologies and the access of the technologies and the marks or registered trade marks of Laird Technologies. The contrast is no request. © Copyright 2010 Laird Technologies, the All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are tade marks or registered trade marks of Laird Technologies to the property of third parties. Nothing herein provides a license under any Laird Technologies or any tind party intellectual property rights.