



Note

- ① - Contact livré non assemblé
Contact delivered unassembled
- ② - Cable compatible: Belden 1855A
Cable compatible: Belden 1855A
- ③ - Outil de sertissage:
Contact intérieur M22520/2-01 avec positionneur M22520/2-35(5)
Contact extérieur M22520/5-01 avec positionneur M22520/5-05B
- ④ - Crimping tool:
Inner contact M22520/2-01 with positioner M22520/2-35(5)
Outer contact M22520/5-01 with positioner M22520/5-05B
- ⑤ - Matières:
- Contact extérieur: inox
- Contact intermédiaire: alliage de cuivre
- Contact intérieur, fut de sertissage et ferule: laiton
- Isolants: PTFE ou équivalent
Material
- Outer contact: Stainless steel
- Intermediary contact: copper alloy
- Inner contact, crimping barrel and ferrule: brass
- Inserts: PTFE or equivalent
- ⑥ - Traitements:
- Contact extérieur: passivation
- Contact intermédiaire, intérieur, fut de sertissage et ferrule: dorure
Finish
- Outer contact: passivation
- Intermediary and inner contact, crimping barrel and ferrule: Gold

Douille coax T8 75 ohms 6G - SDI Socket coax S8 75 ohms 6G-SDI Ref: 612355			
DRAWN BY: M.PRUD'HOM	UPDATED BY: M.LAINE	LAST APPROVED BY: L.LAGRANGE	
ALL DIMENSIONS ARE IN MM	AMPHENOL SOCAPEX		ORIGINAL DRAWING DATE: 30/10/20
SCALE: 7	B.P. 29 74311 THYEZ CEDEX		CONFIGURATION DATA ARE AVAILABLE IN PDM
		REV: B	PAGE: 1/1
172-PLC-251-00			

IN THE CONSTANT PURPOSE OF IMPROVING ITS PRODUCTS, Amphenol Socapex RESERVES THE RIGHT TO MODIFY ANY DIMENSION OR CHARACTERISTICS.
FM.NPD.0036.THYZE.PUNE rev C