



74BCT2241

Octal Buffer/Line Driver with 25Ω Series Resistors in the Outputs

General Description

The 74BCT2241 is an octal buffer and line driver designed to drive the capacitive inputs of MOS memory drivers, address drivers, clock drivers, and bus-oriented transmitters/receivers.


The 25Ω series resistors in the outputs reduce ringing and eliminate the need for external resistors.

Features

- 25Ω series resistors in outputs eliminate the need for external resistors
- TRI-STATE® outputs drive bus lines or buffer memory address registers
- Low I_{CCZ} through BiCMOS techniques
- Guaranteed output skew
- Guaranteed multiple output switching specifications
- Guaranteed 4000V minimum ESD protection
- Guaranteed latchup protection
- Nondestructive hot insertion capability
- High impedance in power down (I_{ZZ} and V_{ID})


Ordering Code: See Section 11

Logic Symbol



TL/F/10895-1

Connection Diagram



TL/F/10895-2

Pin Names	Description
OE ₁	Output Enable Input (Active Low)
OE ₂	Output Enable Input (Active High)
I ₀ -I ₇	Inputs
O ₀ -O ₇	Outputs


2241

Truth Table

\overline{OE}_1	I_{0-3}	O_{0-3}	OE_2	I_{4-7}	O_{4-7}
H	X	Z	L	X	Z
L	H	H	H	H	H
L	L	L	H	L	L

H = HIGH Voltage Level
 L = LOW Voltage Level
 X = Immaterial
 Z = High Impedance

Schematic of Each Output



TL/F/10895-4

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Storage Temperature	-65°C to +150°C
Ambient Temperature under Bias	-55°C to +125°C
Junction Temperature under Bias	
Plastic	-55°C to +150°C
V _{CC} Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30 mA to +5.0 mA

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Voltage Applied to Any Output in the Disable or Power-Off State	-0.5V to +5.5V
in the High State	-0.5V to V _{CC}
Current Applied to Output in LOW State (Max)	Twice the Rated I _{OL} (mA)
ESD Last Passing Voltage (Min)	4000V
DC Latchup Source Current	500 mA
Over Voltage Latchup	V _{CC} + 4.5V

Recommended Operating Conditions

Free Air Ambient Temperature	
Commercial	0°C to +70°C
Supply Voltage	
Commercial	+4.5V to +5.5V

DC Electrical Characteristics

Symbol	Parameter	74BCT			Units	V _{CC}	Conditions
		Min	Typ	Max			
V _{IH}	Input HIGH Voltage	2.0			V		Recognized as a HIGH Signal
V _{IL}	Input LOW Voltage			0.8	V		Recognized as a LOW Signal
V _{CD}	Input Clamp Diode Voltage			-1.2	V	Min	I _{IN} = -18 mA
V _{OH}	Output HIGH Voltage	2.4 2.0			V	Min	I _{OH} = -3 mA I _{OH} = -15 mA
V _{OL}	Output LOW Voltage		0.55 0.8		V	Min	I _{OL} = 3 mA I _{OL} = 15 mA
I _{IH}	Input HIGH Current		5		μA	Max	V _{IN} = 2.7V
I _{BI}	Input HIGH Current Breakdown Test		7		μA	Max	V _{IN} = 7.0V
I _{IL}	Input LOW Current			-250	μA	Max	V _{IN} = 0.5V
I _{OS}	Output Short-Circuit Current	-100		-225	mA	Max	V _{OUT} = 0V
I _{OZH}	Output Leakage Current		20		μA	Max	V _{OUT} = 2.7V
I _{OZL}	Output Leakage Current		-20		μA	Max	V _{OUT} = 0.5V
I _{CEX}	Output HIGH Leakage Current		50		μA	Max	V _{OUT} = V _{CC}
V _{ID}	Input Leakage Test	4.75			V	0.0	I _{ID} = 1.9 μA All Other Pins Grounded
I _{ZZ}	Bus Drainage Test			100	μA	0.0	V _{OUT} = 5.25V
I _{CCH}	Power Supply Current		23	35	mA	Max	V _O = HIGH
I _{CCL}	Power Supply Current		40	60	mA	Max	V _O = LOW
I _{CCZ}	Power Supply Current		6	10	mA	Max	V _O = HIGH Z

2241

AC Electrical Characteristics: See Section 8 for Waveforms and Load Configurations

Symbol	Parameter	74BCT			74BCT		Units	Fig. No.
		T _A = +25°C V _{CC} = +5.0V C _L = 50 pF			V _{CC} = Com V _{CC} = Com C _L = 50 pF			
		Min	Typ	Max	Min	Max		
t _{PLH} t _{PHL}	Propagation Delay Data to Output	1.1 2.0	3.0 3.8	4.4 6.6	1.1 2.0	4.9 6.9	ns	8-3
t _{PZH} t _{PZL}	Output Enable Time	2.7 4.1	5.9 6.8	7.8 9.4	2.7 4.1	8.9 10.3	ns	8-5
t _{PHZ} t _{PLZ}	Output Disable Time	1.7 1.7	4.0 5.2	7.2 9.5	1.7 1.7	8.7 11.3	ns	8-5
t _{OSSL} (Note 1)	Pin to Pin Skew HL Data to Output			1.0		1.2	ns	
t _{OSLH} (Note 1)	Pin to Pin Skew LH Data to Output			0.9		1.1	ns	
t _{OST} (Note 1)	Pin to Pin Skew LH/HL Data to Output			2.0		3.3	ns	
t _{pv} (Note 2)	Device to Device Skew LH/HL Data to Output			3.0		4.0	ns	

Note 1: Skew is defined as the absolute value of the difference between the actual propagation delays for any two separate outputs of the same device. The specification applies to any outputs switching HIGH to LOW (t_{OSSL}), LOW to HIGH (t_{OSLH}), or any combination switching LOW to HIGH and/or HIGH to LOW (t_{OST}). This specification is guaranteed but not tested.

Note 2: Propagation delay variation for a given set of conditions (i.e., temperature and V_{CC}) from device to device. This specification is guaranteed but not tested.

Extended AC Electrical Characteristics: See Section 8 for Waveforms and Load Configurations

Symbol	Parameter	74BCT		74BCT		Units	Fig. No.
		T _A = Com V _{CC} = Com C _L = 50 pF 8 Outputs Switching (Note 1)		T _A = Com V _{CC} = Com C _L = 250 pF (Note 2)			
		Min	Max	Min	Max		
t _{PLH} t _{PHL}	Propagation Delay Data to Output	2.5 3.0	6.0 7.0	3.6 3.6	7.0 10.0	ns	8-3

Note 1: This specification is guaranteed but not tested. The limits apply to propagation delays for all paths described switching in phase (i.e., all low-to-high, high-to-low, etc.).

Note 2: This specification is guaranteed but not tested. The limits represent propagation delays with 250 pF load capacitors in place of the 50 pF load capacitors in the standard AC load. This specification pertains to single output switching only.

Capacitance

Symbol	Parameter	Typ	Units	Conditions
C _{IN}	Input Pin Capacitance	8	pF	V _{CC} = 5.0V
C _{OUT}	Output Pin Capacitance	11	pF	V _{CC} = 5.0V

10