

QSFP Cable Assemblies - QSFP+ 40Gb/s Direct-Attach Copper



For more Information
please call

1-800-Belden1



General Description:

QSFP+ to QSFP+ Direct-Attach Copper, 40Gb/s, Black

Usage (Overall)

Suitable Applications:

Data Centers, Main Equipment Rooms, Telecommunications Rooms, Work Area, 1-10G Ethernet, 1/2/4/8G Fiber Channel, 10G Fiber Channel over Ethernet, SDR, DDR, QDR, FDR-10 Infiniband, Storage Area Networks (SAN), Network Attached Storage (NAS) and High Performance Computing.

Cable Characteristics (Connectivity)

DAC Specs-Length:

Length	# Pairs	AWG	Conductor material	Cable Type	Cable O.D.
0.5 M to 3.0 M	8	30	Solid Copper Silver Plated	Twinax	6.8 mm (0.268 in.)
>3.0 M to 5.0 M	8	26	Solid Copper Silver Plated	Twinax	8.8 mm (0.347 in.)

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Material	Coverage (%)
1	Aluminum Foil-Polyester Tape	100.000
2	Aluminum Braid	85.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Cabling:

Black

Physical Characteristics (Connectivity)

Materials

Materials:

Description	Material	Color
QSFP+ Backshell	Nickel plated zinc alloy diecast	Bright Nickel
QSFP+ Pull Tab	PVC	Green
PCB bare board	Improved FR4 UL94V-0	
PCB Contacts	Gold plated contacts	

Mechanical Characteristics (Connectivity)

Footprint/Type:

QSFP+ to QSFP+

Termination Interface:

Termination	Connection	Durabilities
QSFP+	Mated Connection	100

Cable/Connector Retention:

38.218 lbs.

Plug/Connector Retention:

20.233 lbs.

Insertion Force to Cage:

8.992 lbs.

Withdraw Force from Cage:

6.744 lbs.

QSFSP Cable Assemblies - QSFP+ 40Gb/s Direct-Attach Copper

Storage Temperature Range:	-40°C To +80°C
Installation Temperature Range:	0°C To +70°C
Operating Temperature Range:	0°C To +70°C
Min. Bend Radius (Overall Cable):	1.750 in.
Flex Cycle Rating:	100 min.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

CEC/UL Specification:	CL2
CSA Specification:	FT4
IEEE Specification:	IEEE802.3
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
MIL Order #39 (China RoHS):	Yes
Other Specification:	SFF-8431 (Electrical), SFF-8661 (Mechanical)

Transmission Characteristics (Connectivity)

Electrical Characteristics (Overall)

Electrical Characteristics:

Electrical Parameters	QSFSP-P0M5-1	QSFSP-P1M0-1	QSFSP-P2M0-1	QSFSP-P3M0-1	QSFSP-P5M0-1
Dielectric Strength	300 v	300 v	300 v	300 v	300 v
Current Rating	0.5 A	0.5 A	0.5 A	0.5 A	0.5 A
Insulation Resistance	1000 M-Ohms Min.	1000 M-Ohms Min.	1000 M-Ohms Min.	1000 M-Ohms Min.	1000 M-Ohms Min.
Contact Resistance	50 m-Ohms Max.	50 m-Ohms Max.	50 m-Ohms Max.	50 m-Ohms Max.	50 m-Ohms Max.
ESD (contacts)	1kV	1kV	1kV	1kV	1kV
ESD (direct/air discharge to module)	8KV/16kV	8KV/16kV	8KV/16kV	8KV/16kV	8KV/16kV
Impedance	90 to 110 Ohms	90 to 110 Ohms	90 to 110 Ohms	90 to 110 Ohms	90 to 110 Ohms
Propagation Delay	5.2 nsec/m	5.2 nsec/m	5.2 nsec/m	5.2 nsec/m	5.2 nsec/m
Intra-Pair skew	15 psec/m	15 psec/m	15 psec/m	15 psec/m	15 psec/m
Insertion Loss @5 Ghz	2 dB	3.5 dB	7 dB	10.5 dB	10.5 dB
Difference Waveform Distortion Penalty (dWDPC)	-	1.68 dB	-	3.7 dB	-
Voltage Modulation Amplitude Loss (L)	-	1.07 dB	-	3.5 dB	-
Voltage Modulation Amplitude Loss to Crosstalk Ratio (VCR)	-	38.4 dB	-	37.0 dB	-
AC Common-Mode Voltage (Vcm)	-	8.8 mVrms	-	9.4 mVrms	-
Differential-Mode Return Loss Margin (SDDxx) (0.01-4.1GHz)	-	4.0 dB	-	6.4 dB	-
Differential-Mode Return Loss Margin (SDDxx) (4.1-11.1GHz)	-	3.6 dB	-	3.8 dB	-
Common-Mode Return Loss Margin (SCCxx) (0.01-2.5GHz)	0 dB	0.1 dB	-	0.5 dB	-
Common-Mode Return Loss Margin (SCCxx) (2.5-11.1GHz)	1.0 dB	1.0 dB	-	1.0 dB	-
Common to Differential Mode conversion (SCDxx) (0.01-4.1GHz)	-	13.6 dB	-	14.5 dB	-
Common to Differential Mode conversion (SCDxx) (4.1-11.1GHz)	-	5.8 dB	-	5.2 dB	-

Notes (Overall)

Product Family

Product List:

Belden P/N	Description
SSFPP-P00M5-1	DAC, SFP+ 10Gb/s 0.5M
SSFPP-P01M0-1	DAC, SFP+ 10Gb/s 1M
SSFPP-P02M0-1	DAC, SFP+ 10Gb/s 2M
SSFPP-P03M0-1	DAC, SFP+ 10Gb/s 3M
SSFPP-P05M0-1	DAC, SFP+ 10Gb/s 5M
SSFPP-P07M0-1	DAC, SFP+ 10Gb/s 7M
QSFSP-P00M5-1	DAC, QSFP+ 40Gb/s 0.5M
QSFSP-P01M0-1	DAC, QSFP+ 40Gb/s 1M
QSFSP-P02M0-1	DAC, QSFP+ 40Gb/s 2M
QSFSP-P03M0-1	DAC, QSFP+ 40Gb/s 3M
QSFSP-P05M0-1	DAC, QSFP+ 40Gb/s 5M
QSSFPP-P00M5-1	DAC, QSFP+/4SFP+ 40Gb/s 0.5M
QSSFPP-P01M0-1	DAC, QSFP+/4SFP+ 40Gb/s 1M
QSSFPP-P02M0-1	DAC, QSFP+/4SFP+ 40Gb/s 2M
QSSFPP-P03M0-1	DAC, QSFP+/4SFP+ 40Gb/s 3M
QSSFPP-P05M0-1	DAC, QSFP+/4SFP+ 40Gb/s 5M

Put Ups and Colors:

QQSFP Cable Assemblies - QSFP+ 40Gb/s Direct-Attach Copper

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 03-05-2015

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.