TE Internal #: 6-2271116-2

Standard Circular Connectors, Wire-to-Wire, 12 Position, Sealable, Wire & Cable, Signal, Reverse Gender, A Polarization Code, PA,

Hermetically Sealed

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Wire-to-Wire

Number of Positions: 12

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 2A

Features

Product Type Features

Troduct Type readures	
Assembly Requirement	Factory Assembled
Prewired	No
Assembly Type	Electrical Connector
Circular Connector Shell Type	All Plastic
Connector Product Type	Connector Assembly
Connector System	Wire-to-Wire
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Receptacle
Shell Type	Plastic
Configuration Features	
Number of Positions	12
Number of Power Positions	0
Number of Signal Positions	12

Yes

Contacts Preloaded



Electrical Characteristics

EMI & RFI Protection & Suppression Type	Shielding
Body Features	
Circular Connector Insulation Material Type	PA
Hermetically Sealed	Yes
Contact Features	
Contact Current Rating (Max)	2 A
Reverse Gender	Yes
Circular Connector Contact Type	Socket
Mechanical Attachment	
Polarization Code	A
Mating Alignment Type	1 Key
Mating Retention	With
Housing Features	
Circular Connector Shell Size	20
Dimensions	
Wire Size	.14 – .25 mm², .14 – .25 mm²
Usage Conditions	
IP Water Sealing Level	7
IP Dust Sealing Level	6
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Signal
Shielded	No
Other	
Field Serviceable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

	ith Exemptions
EU ELV Directive 2000/53/EC Compliant w	ith Exemptions



China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (3% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Customers Also Bought





















Documents

Product Drawings

M12, FEMALE, A CODE, 12P, PG9 (AU)

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-2271116-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-2271116-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-2271116-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications

Product Specification

English

Standard Circular Connectors, Wire-to-Wire, 12 Position, Sealable, Wire & Cable, Signal, Reverse Gender, A Polarization Code, PA, Hermetically Sealed

