REV.	DATE	DESCRIPTION
C	04/31/03	UPDATE DRAWING FORMAT



RECOMMENDED CABLE
STRIPPING DIMENSIONS

8				
7				
6				
5	GASKET	SILICONE	RED	1
4	RETAINER RING	BER. COPPER	NATURAL	1
3	CONTACT PIN	BRASS	GOLD	1
2	INSULATOR	TEFLON	NATURAL	1
1	SHELL/BODY	BRASS	GOLD	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	04/31/03
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/132/132102.DWG

Amphenol Connex

PART DESCRIPTION
SMA SEMI–RIGID PLUG
(FOR .141" SEMI–RIGID CABLE)

PART NO. 132102

DWG. NO.	REV.	SIZE	SCALE
132102.DWG	C	A	NA