



Figure similar

Non-reversing motor starter Size 0 Three phase full voltage Solid-state overload relay OLRelay amp range 5.5-22A 110-120/220-240VAC 60HZ coil Combination type 25Amp circuit breaker Encl NEMA type 4X 316 S-steel Water/dust tight noncorrosive Standard width enclosure

|   |   |
|---|---|
| product brand name  | Class 18 & 26   |
| design of the product   | Full-voltage non-reversing motor starter with motor circuit protector |
| special product feature   | ESP200 overload relay; Dual voltage coil                              |
| <b>General technical data</b>   |   |
| Height x Width x Depth [in]   | 24 × 11 × 8 in  |
| touch protection against electrical shock                               | NA for enclosed products  |
| installation altitude [ft] at height above sea level maximum            | 6560 ft   |
| ambient temperature [°F]  |   |
| • during storage  | -22 ... +149 °F   |
| • during operation  | -4 ... +104 °F  |
| ambient temperature   |   |
| • during storage  | -30 ... +65 °C  |
| • during operation  | -20 ... +40 °C  |
| <b>Horsepower ratings</b>   |   |
| yielded mechanical performance [hp] for 3-phase AC motor                |   |
| • at 200/208 V rated value  | 3 hp  |
| • at 220/230 V rated value  | 3 hp  |
| • at 460/480 V rated value  | 0 hp  |
| • at 575/600 V rated value  | 0 hp  |
| <b>Contactors</b>   |   |
| size of contactor   | NEMA controller size 0  |
| number of NO contacts for main contacts                                 | 3   |
| operating voltage for main current circuit at AC at 60 Hz maximum       | 600 V   |
| operational current at AC at 600 V rated value                          | 18 A  |
| mechanical service life (switching cycles) of the main contacts typical | 10000000  |
| <b>Auxiliary contact</b>  |   |
| number of NC contacts at contactor for auxiliary contacts               | 0   |
| number of NO contacts at contactor for auxiliary contacts               | 1   |
| number of total auxiliary contacts maximum                              | 8   |
| contact rating of auxiliary contacts of contactor according to UL       | 10A@600VAC (A600), 5A@600VDC (P600)                                   |
| <b>Coil</b>   |   |
| type of voltage of the control supply voltage                           | AC  |
| control supply voltage  |   |
| • at AC at 60 Hz rated value  | 110 ... 240 V   |
| holding power at AC minimum   | 8.6 W   |

|   |   |
|---|---|
| apparent pick-up power of magnet coil at AC   | 218 VA  |
| apparent holding power of magnet coil at AC   | 25 VA   |
| operating range factor control supply voltage rated value of magnet coil  | 0.85 ... 1.1  |
| percental drop-out voltage of magnet coil related to the input voltage  | 50 %  |
| ON-delay time   | 19 ... 29 ms  |
| OFF-delay time  | 10 ... 24 ms  |
| <b>Overload relay</b>   |   |
| reset function  | Manual, automatic and remote                        |
| trip class  | CLASS 5 / 10 / 20 (factory set) / 30                |
| adjustable current response value current of the current-dependent overload release   | 5.5 ... 22 A  |
| make time with automatic start after power failure maximum  | 3 s   |
| relative repeat accuracy  | 1 %   |
| number of NC contacts of auxiliary contacts of overload relay   | 1   |
| number of NO contacts of auxiliary contacts of overload relay   | 1   |
| operational current of auxiliary contacts of overload relay <ul style="list-style-type: none"> <li>• at AC at 600 V</li> <li>• at DC at 250 V</li> </ul>                          | 5 A<br>1 A  |
| contact rating of auxiliary contacts of overload relay according to UL  | 5A@600VAC (B600), 1A@250VDC (R300)                  |
| insulation voltage (Ui) <ul style="list-style-type: none"> <li>• with single-phase operation at AC rated value</li> <li>• with multi-phase operation at AC rated value</li> </ul> | 600 V<br>300 V                                      |
| <b>Enclosure</b>  |   |
| degree of protection NEMA rating  | 4X, 304 stainless steel                             |
| design of the housing   | dustproof, waterproof & resistant to corrosion      |
| <b>Circuit Breaker</b>  |   |
| type of the motor protection  | Motor circuit protector (magnetic trip only)        |
| operational current of motor circuit breaker rated value  | 25 A  |
| adjustable current response value current of instantaneous short-circuit trip unit  | 55 ... 180 A  |
| <b>Mounting/wiring</b>  |   |
| mounting position   | Vertical  |
| fastening method  | Surface mounting and installation                   |
| type of electrical connection for supply voltage line-side  | Box lug   |
| type of connectable conductor cross-sections at line-side at AWG cables single or multi-stranded  | 1x (14 AWG ... 10 AWG) or 1x (12 AWG ... 10 AWG)    |
| temperature of the conductor for supply maximum permissible   | 75 °C   |
| material of the conductor for supply  | AL or CU  |
| type of electrical connection for load-side outgoing feeder   | Screw-type terminals                                |
| tightening torque [lbf·in] for load-side outgoing feeder  | 20 ... 20 lbf·in                                    |
| type of connectable conductor cross-sections at AWG cables for load-side outgoing feeder single or multi-stranded   | 1x (14 ... 2 AWG)                                   |
| temperature of the conductor for load-side outgoing feeder maximum permissible  | 75 °C   |
| material of the conductor for load-side outgoing feeder   | AL or CU  |
| type of electrical connection of magnet coil  | Screw-type terminals                                |
| tightening torque [lbf·in] at magnet coil   | 5 ... 12 lbf·in                                     |
| type of connectable conductor cross-sections of magnet coil at AWG cables single or multi-stranded  | 2x (16 ... 12 AWG)                                  |
| temperature of the conductor at magnet coil maximum permissible   | 75 °C   |
| material of the conductor at magnet coil  | CU  |
| type of electrical connection for auxiliary contacts  | Screw-type terminals                                |
| tightening torque [lbf·in] at contactor for auxiliary contacts  | 10 ... 15 lbf·in                                    |
| type of connectable conductor cross-sections at contactor   | 1x (12 AWG), 2x (16 ... 14 AWG), 2x (18 ... 16 AWG) |


|  |                      |
|--|----------------------|
| at AWG cables for auxiliary contacts single or multi-stranded  |                      |
| temperature of the conductor at contactor for auxiliary contacts maximum permissible   | 75 °C                |
| material of the conductor at contactor for auxiliary contacts  | CU                   |
| type of electrical connection at overload relay for auxiliary contacts   | Screw-type terminals |
| tightening torque [lbf-in] at overload relay for auxiliary contacts  | 7 ... 10 lbf-in      |
| type of connectable conductor cross-sections at overload relay at AWG cables for auxiliary contacts single or multi-stranded | 2x (20 ... 14 AWG)   |
| temperature of the conductor at overload relay for auxiliary contacts maximum permissible                                    | 75 °C                |
| material of the conductor at overload relay for auxiliary contacts   | CU                   |

**Short-circuit current rating**

|  |                                     |
|--|-------------------------------------|
| design of the short-circuit trip   | Instantaneous trip circuit breaker  |
| breaking capacity maximum short-circuit current (Icu)  |                                     |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 480 V</li> <li>• at 600 V</li> </ul> | 100 kA<br>100 kA<br>25 kA           |
| certificate of suitability   | NEMA ICS 2; UL 508; CSA 22.2, No.14 |

**Further information**

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**  
[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)  
**Industry Mall (Online ordering system)**  
<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mfb=US2:18CUD92XA>  
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
<https://support.industry.siemens.com/cs/US/en/ps/US2:18CUD92XA>  
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=US2:18CUD92XA&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=US2:18CUD92XA&lang=en)  
**Certificates/approvals**  
<https://support.industry.siemens.com/cs/US/en/ps/US2:18CUD92XA/certificate>





last modified:

1/25/2022