776275-1 - ACTIVE

AMP | AMPSEAL TE Internal #: 776275-1 PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 4 mm [.157 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Sealable, AMPSEAL

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > AMPSEAL PCB Headers

Connector System: Wire-to-Board

Number of Positions: 8

Centerline (Pitch): 4 mm [.157 in]

Sealable: Yes

PCB Mount Orientation: Vertical

All AMPSEAL PCB Headers (58)

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Header
Header Type	Fully Shrouded
Connector System	Wire-to-Board
Sealable	Yes

Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	8
PCB Mount Orientation	Vertical
Number of Rows	3
Body Features	
Primary Product Color	Black
Contact Features	
Contact Type	Pin
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	8 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	

PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 4 mm [.157 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Sealable, AMPSEAL



Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	Without
Connector Mounting Type	Fixing Screw
Housing Features	
Centerline (Pitch)	4 mm[.157 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Type	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 4 mm [.157 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Sealable, AMPSEAL



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

TE Part # CAT-AM78-CH8172 AMPSEAL Receptacle Housings

Also in the Series | AMPSEAL

Automotive Connector Caps & Covers (5)	Automotive Connector Locks & Position Assurance(1)	Automotive Housings(31)	Automotive Terminals(8)

Connector Seals & Cavity Plugs(1)	PCB Headers & Receptacles(116)

Customers Also Bought



PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 4 mm [.157 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Sealable, AMPSEAL



TE Part #2-1825910-7 FSM14JH=6MM TACT SWITCH, HIGH TEMP	TE Part #3-794680-4 04P MICRO MNL ASSY,VRT,THRU LF	TE Part #9-2176307-7 RP 1E 0.1W 124K 0.1% 25PPM 5K RL	TE Part #953130-3 12pos MQS .63 header 180deg
TE Part #881545-1 SHUNT LP W/HANDLE 2POS 15AU	TE Part #7-2151434-7 OCEAN_2.0_SPARE_PART_KIT- 054F077F		

Documents

Product Drawings 8POS, PIN DIA 1.3, HDR ASSY, 180DEG, COD 1

English

CAD Files **Customer View Model** ENG_CVM_776275-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_776275-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_776275-1_A.3d_stp.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages AMPSEAL Connector Catalog

English

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

C For support call+1 800 522 6752

PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 4 mm [.157 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Sealable, AMPSEAL



Application Specification

English

Agency Approvals

UL Report

English