


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.

Item No.	Part No.	Description
1	See Table 1	XAF Connector
2	UL10002, 22 AWG	Black
Electrical Specifications		
Current: 3.0A AC/DC		
Voltage: 150V AC/DC		

TABLE 1				
ITEM	NUMBER OF CIRCUITS	CONNECTOR PART NO.	ASSEMBLY PART NO.	TOTAL WIRE REQUIRED
1	2	02XAF-2S	A02XAF02XAF22K254A	563.2 mm
1	3	03XAF-2S	A03XAF03XAF22K254A	844.8 mm
1	4	04XAF-2S	A04XAF04XAF22K254A	1,126.4 mm
1	5	05XAF-2S	A05XAF05XAF22K254A	1,408 mm
1	6	06XAF-2S	A06XAF06XAF22K254A	1,689.6 mm
1	8	08XAF-2S	A08XAF08XAF22K254A	2,252.8 mm
1	10	10XAF-2S	A10XAF10XAF22K254A	2,816 mm
1	20	20XAF-2S	A20XAF20XAF22K254A	5,632 mm



All dimensions are in millimeters with a default tolerance of +/- 5.0 unless otherwise specified.		CUSTOMER NAME		
		DESCRIPTION		
		2.5mm Pitch XAF Standard Catalog Assembly - 10' Overall Length - Pin Out: 1 to 1		
Drawn By: Larissa Mosley	SIZE	CUSTOMER PART NO.	PART NO.	REV
Checked By: Steven Pilkington	SCALE	SEE TABLE 1		
	1:1	DRAWING NO. GAM-547	DATE 6/21/2018	

ZONE	REV	DESCRIPTION	DATE	APPROVED
1	1	Add Electrical Specifications	6/29/2018	LM