2.5 METERS LENGTH





Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 172180 N-Type Plug Right Angle Brass White Bronze + Heatshrink

Connector B

Assembly & Label Notes

Connector A

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



505010.71		4		4 John J.	
132245	Part #:	RG-174	Part #:	172180	
SMA R/A BHD JK RG174 RG316 LMR100	Description:	RG-174 - PE 0.1	Description:	N-Type R/A PLUG RG174 RG316 LMR100 500	
50O	Dielectric:	PE	Type:	N-Type	
SMA	Shielding:	Braid	Gender:	Plug	
Jack	Diameter:	0.1	Body Type:	Right Angle	
Right Angle	Impedance:	50 Ohm	Contact Type:	Solder	
Solder	Sheathing:	None	Polarity:	Standard	
Standard	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
50 Ohm	Length:	2.5 Meters	Mounting:	Cable	
Bulkhead - Rear Mount			Body Material:	Brass	
Brass			Body Finish:	White Bronze	
Gold			IP Rating:	None	
None			Contact Material:	Brass	
Beryllium Copper			Contact Finish:	Gold	
Gold			Max. Freg.:	11 GHz	
12.4 GHz				N-Type Plug Right Angle	
SMA Jack Right Angle			Clocking:	0°	
	SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz	SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz	SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz Description: RG-174 - PE 0.1 Dielectric: PE Shielding: Braid Diameter: 0.1 Impedance: 50 Ohm Sheathing: None Testing: Continuity Hi-Pot Length: 2.5 Meters	SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz Description: RG-174 - PE 0.1 Dielectric: PE Shielding: Braid Diameter: 0.1 Impedance: 50 Ohm Sheathing: None Testing: Continuity Hi-Pot Length: Z.5 Meters Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	

Cable



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-RA-JK/N-RA-PL G174 2.5M

Part No

Q-2P02C00032.5M

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES