

APPLICATOR PARTS LIST

TYPE LENGTHWISE SPLICE CONN. INSULATION PIERCING

AMP INCORPORATED HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER			42	<del>GUARD END</del>		<del>372886</del>	
2	INS. CRIMPER	1	1-570322-5	43	SPRING-SLIDE 3/4 OD	1	2-24017-7	
3	ANVIL	1	1-471359-1	44	FEED PLATE RET.	1	372998	
4	ANVIL SPACER			45				
5	SHEAR BLADE	1	455216-1	46				
6	<del>FEED</del> PLATE - FEED	1	471917-9	47				
7	SHEAR BLADE SPACER			48				
8	FRONT SHEAR PLATE			49	<del>DEPRESSOR TERMINAL</del>		<del>1-692142-1</del>	
9	REAR ANVIL SPACER PLT.			50				
10	FRONT ANVIL SPACER PLT.			51				
11	TOOL SPACER			52				
12	CRIMP SPACER			53				
13	FRONT STRIP GUIDE			54				
14	REAR STRIP GUIDE			55	SG. HD. SET SCR. (DEP.)	1	21077-8	
				56	NUT, HEX.	1	22202-1	
15	RAM	1	471057	57				
16	TOOL HOLDER			58				
17	ADJ. CRIMP MOUNT			59				
18	ADJ. BLOCK			60				
19	APPLICATOR MOUNT ASSY.	1	473933	61				
20	BASE PLATE			62				
21	BASE BLOCK			63				
22	STRIP GUIDE PLATE			64	<del>MECH FEED</del>		<del>1-692140-2</del>	
23	ANVIL HOLDER	1	374348-1	65	TENSION ADJ. PLATE	1	374999	
24	AUX. ANVIL HOLDER				MISCELLANEOUS			
25	STRIPPER	1	376945	66				
26	STRIPPER MOUNT			67				
27	RETAINER PLATE			68				
28	STRIPPER MOUNT BRACKET			69				
29	STRIPPER BUSHING			70				
30	STOCK DRAG	1	372990	71				
31	STOCK DRAG <del>WASHER</del> NUT	1	21022-4	72				
32	STOCK DRAG- <del>STUD</del>	1	21015-8		REV. 0 REL REVISION RECORD	DATE	BY	ECN
33	STOCK DRAG SPRING	1	23846-7	A	REV PER ECN	4-4-73	JE	L-9633
34	STOCK DRAG ADJ. SCREW	2	372997	B	REV PER ECN	6-23-73	JE	L-9832
35	FEED FINGER HOLDER			C	REV PER ECN	2-19-74	JE	R325
36	FEED FINGER	1	811432-1	D	REV PER ECN	7-19-74	JE	R692
37	FEED FINGER TIP			E	REV PER ECN	5/2/83	WDB	R5094
38	FEED FINGER SPACER			F	0150-6332-95	8-95	PM	TS
39	BASE CASTING	1	570238	F1	ECN 0150-1194-04	9-04	WTE	
40	GUARD <del>460582-1</del>	1	<del>694395-1</del>					
41	<del>BRACKET GUARD</del>	1	<del>376946</del>					

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL SPEC 114-2088			485064
WIRE SIZE	CRIMP HEIGHT		
CRIMP	UNTIL TIGHT		
CRIMP	SIZE	TYPE	FEED
WIRE			
INSUL.	.080	0	.266
SLEEVED			
INSULATION RANGE	WIRE RANGE		
.050-.065	22		
EXPLODED VIEW			
A-6010-1 & -2			
REMARKS:			
<div style="border: 1px solid black; padding: 5px;">                     THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.                 </div>			
<div style="border: 1px solid black; padding: 5px;"> <b>RECOMMENDED SPARE PARTS</b> </div>			
THIS APPLICATOR IS TO BE USED ON			
AMP-O-LECTRIC 1-471273-3			
MECH. FEED			DIST.
			4
SERIAL NO.	DATE SHIPPED	DESIGNED	
		R. B. ... 3-26-71	
CUSTOMER NAME AND ADDRESS			CHK'D:
			6-26-71
			APP'D:
			6-25-71
APPLICATOR NUMBER	REV.	SHEET	
F1	566048-1	1 OF 1	

THIS IS A CONTROLLED DOCUMENT.

THIS DRAWING IS UNCLASSIFIED BY AMP INCORPORATED. ALL RIGHTS RESERVED. COPYRIGHT 2006