| NOTES:   | 4. INSTRUCTIONS:  |   | THIRD ANGLE PROJ. 🕀 🖯 | REV DESC                                    |
|--|---|---|-----------------------|---|
| I. MATERIALS AND FINISHES:<br>SMA PLUG - BRASS<br>PROBE CONNECTOR - BRASS & BeCu   | A. TO BE USED WIT<br>B. ALIGN PROBE AN<br>C. DO NOT BEND CA | H SWITCH 902-9049<br>D SWITCH WITHIN IO° MAX.<br>BLE WHEN TESTING |                       | A RELEAS                                    |
| CABLE - RG-178 COAXIAL CABLE   | 5. PACKAGING  |   |                       |   |
| 2. ELECTRICAL:<br>A.IMPEDANCE : $50\Omega$   | A. QUANTITY: SING<br>B. MARKING : BAG<br>"AMPHENOL RE       |   |                       |   |
| 3. PROBE MECHANICAL PERFORMANCE<br>A.TEMP.RANGE : -40°C~+85°C<br>B.INSERTION FORCE : 30N MAX<br>C.CABLE AXIAL HOLDING FORCE : 30N MIN<br>D.DURABILITY : 5000 CYCLES MAX<br>E.WITHDRAWAL FORCE : 5N MIN. TO 40N MAX   |   | US OUC FOUT AND DATE CODE   |                       |   |
|  |   |   |                       |   |
| -  |   | 250.00±5.00   |                       |   |
| 20.00<br>TYP(2)  | 1   |   |                       |   |
|  |   | -RG-178 COAXIAL CABLE   |                       |   |
|  | /<br>1 /  |   |                       |   |
|  |   |   |                       |   |
|  | -   |   |                       |   |
|  |   |   |                       |   |
| SMA STR PLUG HEAT ST<br>TYP(2)   | TRINK TUBE  |   |                       |   |
|  |   |   |                       |   |
|  |   |   |                       |   |
|  |   |   |                       |   |
| DESIGN REQUIREMENTS:   |   |   |                       |   |
| X FREQUENCY : DC TO 6 GHz  |   |   |                       |   |
| X VSWR : I.6 MAX (DC TO 3 GHz)<br>2.0 MAX (3 TO 6 GHz)<br>X INS. LOSS : I.5 dB MAX (DC TO 3 GHz)   | HI-POT :  |   |                       | CUETO                                       |
| 2.5 dB MAX (3 TO 6 GHz)  |   |   |                       |   |
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TO<br><0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm<br>±0.05mm ±0.1mm ±0.2mm ± 0.3mm   | ANGLES  | DRAWN<br>MOHAN  | DATE<br>09 - May - 14 | TITLE<br>SMA PLUG TO                        |
| NOTICE - These drawings, specifications, or other data (1) are, and<br>property of Amphenol corp. (2) must be returned upon request; and (<br>confidential and not to be disclosed to any person other than those  | remain the<br>3) are<br>to whom they                        | ENGINEER<br>MOHAN   | DATE<br>09-May-I4     | PROBE PLUG<br>USING COAXIAL CABLE           |
| NOTICE - These drawings, specifications, or other data (1) are, and<br>property of Amphenol corp. (2) must be returned upon request; and (<br>confidential and not to be disclosed to any person other than those<br>are given by Amphenol Corp. the furnishing of these drawings, speci<br>other data by Amphenol Corp., or to any other person to anyone for a<br>not to be regarded by implication or otherwise in any manner licensi<br>rights to permitting such holder or any other person to manufacture,<br>product, process or design, patented or otherwise, that may in any w<br>or disclosed by said drawings, specifications, or other data | fications, or<br>ny purpose is<br>ng, granting EAR 7770     | APPROVED<br>K. CAPOZZ   | DATE<br>I II-Jan-18   | 250.00 MM LENGTH<br>SCALE: 2.8:1.0 SHEET 20 |
| rights to permitting such holder or any other person to manufacture,<br>product, process or design, patented or otherwise, that may in any w<br>or disclosed by said drawings, specifications, or other data.  | use or sell any<br>cay be related to<br>FINISH              |   |                       | DWG SIZE<br>B                               |
|  | FINISH  |   |                       |   |

