# 1744037-3 ACTIVE

### **Economy Power**

TE Internal #: 1744037-3

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 3 Position, 5.08 mm [.2 in] Centerline, Printed Circuit Board, UL 94V-0,

Economy Power

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Header

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 3

Centerline (Pitch): 5.08 mm [.2 in]

### **Features**

### **Product Type Features**

| Header Type                       | Partially Shrouded    |
|-----------------------------------|-----------------------|
| Rectangular Power Connector Type  | Header                |
| Connector & Housing Type          | Plug                  |
| Connector System                  | Wire-to-Board         |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |
| Configuration Features            |                       |
| Number of Positions               | 3                     |
| PCB Mount Orientation             | Vertical              |
| Number of Power Positions         | 3                     |
| Number of Rows                    | 1                     |
| Electrical Characteristics        |                       |

250 VDC

Operating Voltage



| PCB Contact Termination Area Plating Material Thickness | .8 μm, 1 μm[31.49 μin][39.37 μin] |
|---|-----------------------------------|
| Contact Layout  | Inline                            |
| Contact Mating Area Plating Material                    | Tin                               |
| Contact Base Material                                   | Copper Alloy                      |
| Contact Current Rating (Max)                            | 8 A                               |
| Contact Retention Within Housing                        | Without                           |
| Contact Type  | Pin                               |
| PCB Contact Termination Area Plating Material           | Tin                               |
| Contact Mating Area Plating Material Thickness          | 2.03 μm[80 μin]                   |
| Termination Features                                    |                                   |
| Termination Post & Tail Length                          | 3.7 mm[.146 in]                   |
| Termination Method to Printed Circuit Board             | Through Hole - Solder             |
| Mechanical Attachment                                   |                                   |
| Strain Relief   | Without                           |
| Mating Retention  | With                              |
| Mating Alignment  | With                              |
| PCB Mount Alignment                                     | Without                           |
| Panel Mount Feature                                     | Without                           |
| PCB Mount Retention                                     | Without                           |
| Mating Retention Type                                   | Latch                             |
| Connector Mounting Type                                 | Board Mount                       |
| Housing Features  |                                   |
| Centerline (Pitch)                                      | 5.08 mm[.2 in]                    |
| Housing Color   | Natural                           |
| Housing Material  | Nylon 66                          |
| Dimensions  |                                   |
| Connector Height  | 10.9 mm[.429 in]                  |
| PCB Thickness (Recommended)                             | .06 mm[1.6 in]                    |
| Product Width   | 8.2 mm[.323 in]                   |
| Product Length  | 12.76 mm[.502 in]                 |
| Usage Conditions  |                                   |
| Operating Temperature Range                             | -25 – 105 °C[-13 – 221 °F]        |



#### **Operation/Application**

| Circuit Application    | Power                         |
|------------------------|-------------------------------|
| Industry Standards     |                               |
| UL Flammability Rating | UL 94V-0                      |
| Glow Wire Rating       | Standard Part - Not Glow Wire |
| Packaging Features     |                               |
| Packaging Quantity     | 1000                          |
| Packaging Method       | Bag                           |

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                                 |
| Solder Process Capability                     | Wave solder capable to 240°C  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### Compatible Parts





## Also in the Series | Economy Power




Connector Contacts(1)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(162)



PCB Latches, Locks & Retainers(2)



Power Contacts(8)




Rectangular Connector Housings(1)



Rectangular Power Connectors (302)



Wire-to-Board Connector Assemblies & Housings(142)



# Customers Also Bought



TE Part #5-1775443-6
EMIX CONN., 1.5MM PITCH, HDR, V
/T, 6P





1MM FPC HORZ.TOP CONT.ASSY 10P



TE Part #1376164-1 BATTERY HOLDER ML621 ASSY











### **Documents**

### **Product Drawings**

03P EC PWR.200 CL HDR ASSY VRT

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1744037-3\_O.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1744037-3\_O.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1744037-3\_O.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

1-1773885-9 Economy Power Connectors

English

### **Product Specifications**

**Application Specification** 

English

**Application Specification** 

Japanese

### **Product Environmental Compliance**

**TE Material Declaration** 

English

### **Agency Approvals**

**UL Report** 

English