



1 Amp Ultra Low Forward Voltage Schottky Rectifier

LSM115J



	Dim. Inches		Millimeter		
	Minimum	Maximum	Minimum	Maximum	Notes
A	.073	.087	1.85	2.21	
B	.160	.180	4.06	4.57	
C	.130	.155	3.30	3.94	
D	.205	.220	5.21	5.59	
E	.075	.130	1.91	3.30	
F	.030	.060	.760	1.52	



DO-214BA Package

Microsemi Catalog Number	Industry Part Number	Working Peak Reverse Voltage	Repetitive Peak Reverse Voltage
LSM115J	10BQQ15	15V	15V

- Schottky Barrier Rectifier
- Guard Ring For Reverse Protection
- Low Power Loss, High Efficiency
- 100°C Junction Temperature
- V_{RRM} 15V
- High Surge Capability
- V_f Less than .2V @ 1A @ 100°C
- Schottky OR'ing diode

Electrical Characteristics

Average forward current	$I_F(AV)$ 1 Amps	$T_L = 65^\circ\text{C}$, Square wave, $R_{\theta JL} = 15^\circ\text{C}/\text{W}$
Maximum surge current	I_{FSM} 50 Amps	8.3ms, half sine, $T_J = 100^\circ\text{C}$
Maximum peak forward voltage	V_{FM} 0.22 Volts	$I_{FM} = 1.0\text{A}; T_J = 75^\circ\text{C}^*$
Maximum peak reverse current	I_{RM} 10 mA	$V_{RRM} = 15\text{V}, T_J = 25^\circ\text{C}$
Typical junction capacitance	C_J 150pF	$T_J = 25^\circ\text{C}, V_R = 5\text{V}$

*Pulse test: Pulse width 300 μsec . Duty cycle 2%

Thermal and Mechanical Characteristics

Storage temperature range	T_{STG}	-55°C to 150°C
Operating junction temp range	T_J	-55°C to 100°C
Maximum thermal resistance	$R_{\theta JL}$	15°C/W Junction to Lead
Weight		.0047 ounces (.013 grams) typical

LSM115J

Figure 1
Typical Forward Characteristics




Figure 3
Typical Junction Capacitance




Figure 2
Typical Reverse Characteristics

