



35ACPE_4 series

35W - Single Output AC-DC Converter - Enclosed Switching - Universal Input - Isolated

AC-DC Converter

35 Watt

- ⊕ Universal 85 - 264VAC or 120 - 373VDC input voltage
- ⊕ Accepts AC or DC input (dual-use of same terminal)
- ⊕ Operating ambient temperature range: -30°C to +70°C
- ⊕ Low standby power consumption, high efficiency
- ⊕ High I/O isolation test voltage up to 4000VAC
- ⊕ Low ripple & noise
- ⊕ Output short circuit, over-current, over-voltage protection
- ⊕ IEC/EN/UL62368, IEC/EN60335, GB4943, IEC/EN61558 safety approved
- ⊕ Withstand 300VAC surge input for 5s
- ⊕ Over-voltage class III (designed to meet EN61558)
- ⊕ Withstand 5G vibration test
- ⊕ Operating altitude up to 5000m

The 35ACPE_4 is one of GAPTEC's enclosed AC-DC switching power supply. It features universal AC input and at the same time accepts DC input voltage, cost-effective, low no load power consumption, high efficiency, high reliability and double or reinforced insulation. These converters offer excellent EMC performance and meet IEC/EN61000-4, CISPR32/EN55032, IEC/UL/EN62368, EN60335, EN61558, GB4943 standards and they are widely used in areas of industrial, LED, street light control, electricity, security, telecommunications, smart home etc.



Common specifications					
Item	Test conditions	Min	Typ	Max	Units
Short circuit protection	recovery time <5s after the short circuit disappear	Hiccup, continuous, self-recovery			
Operating temperature		-30		+70	°C
Storage temperature		-40		+85	°C
Storage humidity	Non-condensing			95	%RH
Operating humidity	Non-condensing	20		90	%RH
Switching Frequency			65		kHz
Power derating	Operating temp derating				
	• -30 to -25°C/ 85-100VAC • +50°C to +70°C	5			%/°C
	Input voltage derating				
	• 85VAC-100VAC	1.33			%/VAC
Safety standard	IEC/EN/UL62368/IEC/EN60335/GB4943/IEC/EN61558				
Safety certification	IEC/EN/UL62368/IEC/EN60335/GB4943/IEC/EN61558				
Safety class	CLASS I				
MTBF	MIL-HDBK-217F@25°C	>300,000 h			
Case Material	Metal (AL1100, SGCC)				
Dimensions	99.00 x 82.00 x 30.00 mm				
Weight	170g TYP.				
Cooling Method	Free air convection				

Input specifications					
Item	Test conditions	Min	Typ	Max	Units
Input Voltage Range	• AC input	85		264	VAC
	• DC input	120		373	VDC
Input frequency		47		63	Hz
Input current	• 115VAC			0.8	A
	• 230VAC			0.6	A
Inrush current (Cold start)	• 115VAC		30		A
	• 230VAC		50		A
Leakage current	277VAC	<0.75mA			
Hot plug	Unavailable				

Output specifications					
Item	Test conditions	Min	Typ	Max	
Output voltage accuracy	Full load range				
		• 5V		±2.0	%
	• 12V/15V/24V		±1.0		%
Line regulation	Rated load		±0.5		%
Load regulation	0% - 100% load				
		• 5V		±1	%
	• 12V/15V/24V		±0.5		%
Ripple & noise*	20MHz bandwidth; peak-to-peak value				
		• 5V		80	mV
		• 12V/15V		120	mV
		• 24V		150	mV
Temperature coefficient			±0.03		%/°C
Minimum load		0			%
Stand-by power consumption				0.3	W
Hold-up time	• 115VAC • 230VAC		8		ms
			30		ms

*The "Tip and barrel method" is used for ripple and noise test, output parallel 47uF electrolytic capacitor and 0.1uF ceramic capacitor, please refer to Enclosed Switching Power Supply Application Notes for specific information.

Example: 35ACPE_24S4

35 = 35Watt; AC = AC-DC; PE = series;
24 = 24Vout; S = single output, 4 = 4kVAC isolation

Note:

1. Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta = 25°C, humidity <75%RH with nominal input voltage and rated output load;
2. The room temperature derating of 5°C/1000m is needed for operating altitude greater than 2000m;
3. All index testing methods in this datasheet are based on our company corporate standards
4. In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability;
5. We can provide product customization service..
6. Products are related to laws and regulations: see "Features" and "EMC";
7. The out case needs to be connected to the earth of system when the terminal equipment in operating;
8. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units;

35ACPE_4 series

35W - Single Output AC-DC Converter - Enclosed Switching - Universal Input - Isolated

Protection specifications	
Over-current protection	110%-200% I _o , self-recovery
Over-voltage protection	<ul style="list-style-type: none"> • 5V ≤ 6.3VDC (Output voltage clamp or hiccup) • 12V ≤ 16.2VDC (Output voltage clamp or hiccup) • 15V ≤ 21.75VDC (Output voltage clamp or hiccup) • 24V ≤ 33.6VDC (Output voltage clamp or hiccup)

Isolation specifications					
Item	Test condition	Min	Typ	Max	Units
Isolation test	• Input	2000			VAC
	• Input-output	4000			VAC
	• Output	1250			VAC
Insulation resistance	At 500VDC				
	• Input	100			MΩ
	• Input-output	100			MΩ
	• Output	100			MΩ



EMC specifications				
Emissions	CE	CISPR32/EN55032	CLASS B	
Emissions	RE	CISPR32/EN55032	CLASS B	
Emissions	Harmonic current	IEC/EN61000-3-2	CLASS A	
Immunity	ESD	IEC/EN61000-4-2	Contact ±6KV/Air ±8KV	perf. Criteria A
Immunity	RS	EC/EN61000-4-3	10V/m	perf. Criteria A
Immunity	EFT	IEC/EN61000-4-4	±2KV	perf. Criteria A
Immunity	Surge	IEC/EN61000-4-5	line to line ±1KV/line to ground ±4KV	perf. Criteria A
Immunity	CS	IEC/EN61000-4-6	10Vr.m.s	perf. Criteria A
Immunity	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11	0%,70%	perf. Criteria B

Product Selection Guide

Approval	Model	Output Power [W]	Nominal Output Voltage and Current [Vo/Io]	Output Voltage Adjustable Range (V)	Efficiency at 230VAC [% , typ]	Max. Capacitive Load (μF)
UL	35ACPE_05S4	35	5V/7A	4.5-5.5	83	8000
UL	35ACPE_12S4	36	12V/3A	10.2-13.8	87	1500
UL	35ACPE_15S4	36	15V/2.4A	13.5-18	89	1000
UL	35ACPE_24S4	36	24V/1.5A	21.6-28.8	88	750



Please note: *Use suffix "/C" for terminal with protective cover (35ACPE_24S4/C) and suffix "/Q" for conformal coating (35ACPE_24S4/Q).

Product Characteristic Curve



1. With an AC input voltage between 85-100VAC and a DC input between 120-140VDC the output power must be derated as per the temperature derating curves;
2. This product is suitable for applications using natural air cooling; for applications in closed environment please consult FAE.


Efficiency



35ACPE_4 series

35W - Single Output AC-DC Converter - Enclosed Switching - Universal Input - Isolated

Dimensions and recommended layout - Conformal coating



Dimensions and recommended layout - Terminal with protective cover

