2.5 METERS LENGTH



Connector A 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel 50 Ohm RG-174 Continuity/Hi-Pot Connector B 082-6575 N-Type Jack Straight Bulkhead - Rear Mount Brass Nickel IP67 + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A			Cable		Connector B		
Part #: Description Type: Gender: Body Typ Contact T Polarity: Impedance Mounting Body Mat Body Fini IP Rating Contact F Max. Free Booting:	112234 n: BNC Clamp BHE BNC Jack Straight ype: Crimp Standard e: 50 Ohm Bulkhead - Rear bulkhead - Rear starial: Brass sh: Nickel None aterial: Beryllium Coppe nish: Silver : 4 GHz	BNC Clamp BHD JK RG188 500 BNC Jack Straight Crimp Standard 50 Ohm Bulkhead - Rear Mount Brass Nickel None Beryllium Copper Silver		RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 2.5 Meters	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	082-6575 N-Type BHD JK RG N-Type Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mo Brass Nickel IP67 Beryllium Copper Gold 11 GHz	N-Type BHD JK RG316 IP67 500 N-Type Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Nickel IP67 Beryllium Copper Gold 11 GHz N-Type Jack Straight BHD	
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CONV		PROPRIETARY INFORMATIC FOR ANY PURPOSE DETRIM INC. IT MAY NOT BE REPROI IN ANY FORM WITHOUT TH CUSTOM CABLE INC. ACCEPT	PRAWING MAY CONTAIN PATENTED OR IETARY INFORMATION AND MUST NOT BE USED NY PURPOSE DETRIMENTAL TO CUSTOM CABLE MAY NOT BE REPRODUCED OR TRANSCRIBED Y FORM WITHOUT THE WRITTEN CONSENT OF M CABLE INC. ACCEPTANCE OF THIS DRAWING ILISHES AND AGREEMENT OF THE FOREGOING.		Title: BNC-ST-JK/N-ST-JK G174 2.5M Part No: Q-0401U00032.5M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	