


TrenchMV™ Power MOSFET

IXTH152N085T
IXTQ152N085T


V_{DSS} = 85 V
I_{D25} = 152 A
R_{DS(on)} ≤ 7.0 mΩ

N-Channel Enhancement Mode
Avalanche Rated




| Symbol | Test Conditions | Maximum Ratings | |
|-------------------|---|-----------------|-----------|
| V _{DSS} | T _J = 25°C to 175°C | 85 | V |
| V _{DGR} | T _J = 25°C to 175°C; R _{GS} = 1 MΩ | 85 | V |
| V _{GSM} | Transient | ± 20 | V |
| I _{D25} | T _C = 25°C | 152 | A |
| I _{LRMS} | Lead Current Limit, RMS | 75 | A |
| I _{DM} | T _C = 25°C, pulse width limited by T _{JM} | 410 | A |
| I _{AR} | T _C = 25°C | 25 | A |
| E _{AS} | T _C = 25°C | 750 | mJ |
| dv/dt | I _S ≤ I _{DM} , di/dt ≤ 100 A/μs, V _{DD} ≤ V _{DSS} T _J ≤ 175°C, R _G = 5 Ω | 3 | V/ns |
| P _D | T _C = 25°C | 360 | W |
| T _J | | -55 ... +175 | °C |
| T _{JM} | | 175 | °C |
| T _{stg} | | -55 ... +175 | °C |
| T _L | 1.6 mm (0.062 in.) from case for 10 s | 300 | °C |
| T _{SOLD} | Plastic body for 10 seconds | 260 | °C |
| M _d | Mounting torque | 1.13 / 10 | Nm/lb.in. |
| Weight | TO-3P TO-247 | 5.5 6 | g g |

TO-247 (IXTH)



TO-3P (IXTQ)



G = Gate D = Drain
S = Source TAB = Drain

| Symbol | Test Conditions (T _J = 25°C unless otherwise specified) | Characteristic Values | | |
|---------------------|---|------------------------|----------|------|
| | | Min. | Typ. | Max. |
| BV _{DSS} | V _{GS} = 0 V, I _D = 250 μA | 85 | | V |
| V _{GS(th)} | V _{DS} = V _{GS} , I _D = 250 μA | 2.0 | | V |
| I _{GSS} | V _{GS} = ± 20 V, V _{DS} = 0 V | | ± 200 | nA |
| I _{DSS} | V _{DS} = V _{DSS} V _{GS} = 0 V | T _J = 150°C | 5 250 | μA |
| R _{DS(on)} | V _{GS} = 10 V, I _D = 25 A, Notes 1, 2 | 5.5 | 7.0 | mΩ |

Features

- Ultra-low On Resistance
- Unclamped Inductive Switching (UIS) rated
- Low package inductance
 - easy to drive and to protect
- 175 °C Operating Temperature

Advantages

- Easy to mount
- Space savings
- High power density

Applications


- Automotive
- Motor Drives
- 42V Power Bus
- ABS Systems
- DC/DC Converters and Off-line UPS
- Primary Switch for 24V and 48V Systems
- High Current Switching Applications

| Symbol | Test Conditions | Characteristic Values | | |
|--------------|---|-----------------------|------|------|
| | ($T_J = 25^\circ\text{C}$ unless otherwise specified) | Min. | Typ. | Max. |
| g_{fs} | $V_{DS} = 10 \text{ V}; I_D = 60 \text{ A}$, Note 1 | 60 | 100 | S |
| C_{iss} | | 5500 | | pF |
| C_{oss} | $V_{GS} = 0 \text{ V}, V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}$ | 720 | | pF |
| C_{rss} | | 150 | | pF |
| $t_{d(on)}$ | Resistive Switching Times | | 30 | ns |
| t_r | $V_{GS} = 10 \text{ V}, V_{DS} = 0.5 \text{ V}_{DSS}, I_D = 25 \text{ A}$ | 50 | | ns |
| $t_{d(off)}$ | $R_G = 5 \Omega$ (External) | 50 | | ns |
| t_f | | 45 | | ns |
| $Q_{g(on)}$ | | 114 | | nC |
| Q_{gs} | $V_{GS} = 10 \text{ V}, V_{DS} = 0.5 \text{ V}_{DSS}, I_D = 25 \text{ A}$ | 30 | | nC |
| Q_{gd} | | 35 | | nC |
| R_{thJC} | | | 0.42 | °C/W |
| R_{thCS} | | 0.25 | | °C/W |

Source-Drain Diode


| Symbol | Test Conditions | Characteristic Values | | |
|----------|--|-----------------------|------|------|
| | ($T_J = 25^\circ\text{C}$ unless otherwise specified) | Min. | Typ. | Max. |
| I_s | $V_{GS} = 0 \text{ V}$ | | 152 | A |
| I_{SM} | Pulse width limited by T_{JM} | | 410 | A |
| V_{SD} | $I_F = 25 \text{ A}, V_{GS} = 0 \text{ V}$, Note 1 | | 1.0 | V |
| t_{rr} | $I_F = 25 \text{ A}, -di/dt = 100 \text{ A}/\mu\text{s}$ $V_R = 40 \text{ V}, V_{GS} = 0 \text{ V}$ | 90 | | ns |

Notes: 1. Pulse test, $t \leq 300 \mu\text{s}$, duty cycle $d \leq 2\%$;
 2. On through-hole packages, $R_{DS(on)}$ Kelvin test contact location must be 5 mm or less from the package body.

TO-247AD Outline

Terminals: 1 - Gate 2 - Drain Tab - Drain

| Dim. | Millimeter | | Inches | |
|----------------|------------|-------|--------|-------|
| | Min. | Max. | Min. | Max. |
| A | 4.7 | 5.3 | .185 | .209 |
| A ₁ | 2.2 | 2.54 | .087 | .102 |
| A ₂ | 2.2 | 2.6 | .095 | .098 |
| b | 1.0 | 1.4 | .040 | .055 |
| b ₁ | 1.65 | 2.13 | .065 | .084 |
| b ₂ | 2.87 | 3.12 | .113 | .123 |
| C | .4 | .8 | .016 | .031 |
| D | 20.80 | 21.46 | .819 | .845 |
| E | 15.75 | 16.26 | .610 | .640 |
| e | 5.20 | 5.72 | 0.205 | 0.225 |
| L | 19.81 | 20.32 | .780 | .800 |
| L ₁ | | 4.50 | | .177 |
| ØP | 3.55 | 3.65 | .140 | .144 |
| Q | 5.89 | 6.40 | 0.232 | 0.252 |
| R | 4.32 | 5.49 | .170 | .216 |
| S | 6.15 | BSC | 242 | BSC |

TO-3P (IXTQ) OutlinePins: 1 - Gate 2 - Drain
3 - Source 4, TAB - Drain

| SYM | INCHES | | MILLIMETERS | |
|-----------------|--------|------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | .185 | .193 | 4.70 | 4.90 |
| A ₁ | .051 | .059 | 1.30 | 1.50 |
| A ₂ | .057 | .065 | 1.45 | 1.65 |
| b | .035 | .045 | 0.90 | 1.15 |
| b ₂ | .075 | .087 | 1.90 | 2.20 |
| b ₄ | .114 | .126 | 2.90 | 3.20 |
| c | .022 | .031 | 0.55 | 0.80 |
| D | .780 | .791 | 19.80 | 20.10 |
| D ₁ | .665 | .677 | 16.90 | 17.20 |
| E | .610 | .622 | 15.50 | 15.80 |
| E ₁ | .531 | .539 | 13.50 | 13.70 |
| e | .215 | BSC | 5.45 | BSC |
| L | .779 | .795 | 19.80 | 20.20 |
| L ₁ | .134 | .142 | 3.40 | 3.60 |
| ØP | .126 | .134 | 3.20 | 3.40 |
| ØP ₁ | .272 | .280 | 6.90 | 7.10 |
| S | .193 | .201 | 4.90 | 5.10 |

All metal area are tin plated.


PRELIMINARY TECHNICAL INFORMATION

The product presented herein is under development. The Technical Specifications offered are derived from data gathered during objective characterizations of preliminary engineering lots; but also may yet contain some information supplied during a pre-production design evaluation. IXYS reserves the right to change limits, test conditions, and dimensions without notice.


IXYS reserves the right to change limits, test conditions, and dimensions.

IXYS MOSFETs and IGBTs are covered by 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 one or more of the following U.S. patents: 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537


**Fig. 1. Output Characteristics
@ 25°C**




**Fig. 2. Extended Output Characteristics
@ 25°C**



**Fig. 3. Output Characteristics
@ 150°C**



**Fig. 4. $R_{DS(on)}$ Normalized to $I_D = 76A$ Value
vs. Junction Temperature**



**Fig. 5. $R_{DS(on)}$ Normalized to $I_D = 76A$ Value
vs. Drain Current**




Fig. 6. Drain Current vs. Case Temperature












Fig. 7. Input Admittance

Fig. 8. Transconductance

Fig. 9. Forward Voltage Drop of Intrinsic Diode

Fig. 10. Gate Charge

Fig. 11. Capacitance

Fig. 12. Maximum Transient Thermal Impedance



**Fig. 13. Resistive Turn-on
Rise Time vs. Junction Temperature**




**Fig. 14. Resistive Turn-on
Rise Time vs. Drain Current**




**Fig. 15. Resistive Turn-on
Switching Times vs. Gate Resistance**



**Fig. 16. Resistive Turn-off
Switching Times vs. Junction Temperature**



**Fig. 17. Resistive Turn-off
Switching Times vs. Drain Current**



**Fig. 18. Resistive Turn-off
Switching Times vs. Gate Resistance**

