

MJD44H11T4-A MJD45H11T4-A

Complementary power transistors

Features

- The devices are qualified for automotive application
- Low collector-emitter saturation voltage
- Fast switching speed
- Surface-mounting TO-252 (DPAK) power package in tape and reel (suffix "T4")

Applications

- Power amplifier
- Switching circuits

Description

The devices are manufactured in low voltage multi epitaxial planar technology. They are intended for general purpose linear and switching applications.




Figure 1. Internal schematic diagram




Table 1. Device summary

Order codes	Marking	Polarity	Package	Packaging
MJD44H11T4-A	MJD44H11	NPN	DPAK	Tape and reel
MJD45H11T4-A	MJD45H11	PNP	DPAK	Tape and reel

1/8

1 Absolute maximum ratings

Table 2. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V _{CEO}	Collector-emitter voltage (I _B = 0)	80	V
V _{EBO}	Emitter-base voltage (I _C = 0)	5	V
Ι _C	Collector current	8	A
I _{CM}	Collector peak current	16	А
P _{TOT}	Total dissipation at T _{case} = 25 °C	20	W
T _{STG}	Storage temperature	-55 to 150	°C
TJ	Max. operating junction temperature	150	°C

Note: For PNP types voltage and current values are negative.

Table 3.Thermal data

Symbol	Parameter	Value	Unit
R _{thJC}	Thermal resistance junction-case max	6.25	°C/W

2 Electrical characteristics

 T_{case} = 25 °C; unless otherwise specified.


Table 4.Electrical characteristics

Symbol	Parameter	Test conditions		Min.	Тур.	Max.	Unit
V _{CEO(sus)} ⁽¹⁾	Collector-emitter sustaining voltage (I _B = 0)	I _C = 30 mA		80	-		V
ICES	Collector cut-off current (V _{BE} = 0)	V _{CE} = 80 V			-	10	μA
I _{EBO}	Emitter cut-off current (I _C = 0)	V _{EB} = 5 V			-	50	μA
V _{CE(sat)} ⁽¹⁾	Collector-emitter saturation voltage	I _C = 8 A	I _B = 0.4 A		-	1	v
V _{BE(sat)} ⁽¹⁾	Base-emitter saturation voltage	I _C = 8 A	I _B = 0.8 A		-	1.5	v
h _{FE} ⁽¹⁾	DC current gain	I _C = 2 A	$V_{CE} = 1 V$	60	-		
		$I_C = 4 A$	$V_{CE} = 1 V$	40	-		

1. Pulse test: pulse duration \leq 300 µs, duty cycle \leq 2 %.

Note: For PNP types voltage and current values are negative.

2.1 Typical characteristic (curves)









Figure 6. Collector-emitter saturation voltage (NPN)

Figure 7. Collector-emitter saturation voltage (PNP)






3 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK[®] packages, depending on their level of environmental compliance. ECOPACK[®] specifications, grade definitions and product status are available at: *www.st.com*. ECOPACK[®] is an ST trademark.



DIM. min. typ max. A 2.20 2.40 A1 0.90 1.10 A2 0.03 0.23 b 0.64 0.90 b 0.64 0.90 c 0.45 0.60 c2 0.48 0.60 c2 0.48 0.60 D 6.00 6.20 D1 5.10 6.60 E 6.40 6.60 E1 4.70 6.60 H 9.35 10.10 L1 2.80 10.10 L1 2.80 10.10 L2 0.80 1 V2 0° 8°		TO-252 (DPAK) mechanical data				
min. typ max. A 2.20 2.40 A1 0.90 1.10 A2 0.03 0.23 b 0.64 0.90 b4 5.20 5.40 c 0.45 0.60 c2 0.48 0.60 D 6.00 6.20 D1 5.10 6.60 E1 4.70 6.60 e1 4.40 4.60 H 9.35 10.10 L1 2.80 12 L1 2.80 1 R 0.60 1	DIM		mm.			
A1 0.90 1.10 A2 0.03 0.23 b 0.64 0.90 b4 5.20 5.40 c 0.45 0.60 c2 0.48 0.60 D 6.00 6.20 D1 5.10 6.60 E 6.40 6.60 E1 4.70 6.60 H 9.35 10.10 L1 2.80 10.10 L2 0.60 1 R 0.60 1	DIM.	min.	typ	max.		
A2 0.03 0.23 b 0.64 0.90 b4 5.20 5.40 c 0.45 0.60 c2 0.48 0.60 D 6.00 6.20 D1 5.10 6.60 E 6.40 6.60 E1 4.70 6.60 H 9.35 10.10 L 1 2.80 1 L1 2.80 1 1 R 0.60 1 1	A	2.20		2.40		
b 0.64 0.90 b4 5.20 5.40 c 0.45 0.60 c2 0.48 0.60 D 6.00 6.20 D1 5.10 6.60 E 6.40 6.60 E1 4.70 6.60 H 9.35 10.10 L 1 10.10 L2 0.60 1 R 0.60 1	A1	0.90		1.10		
b4 5.20 5.40 c 0.45 0.60 c2 0.48 0.60 D 6.00 6.20 D1 5.10 6.60 E 6.40 6.60 E1 4.70 6.60 e1 4.40 4.60 H 9.35 10.10 L1 2.80 1.1 L2 0.60 1 R 0.60 1	A2	0.03		0.23		
c 0.45 0.60 c2 0.48 0.60 D 6.00 6.20 D1 5.10 6.60 E 6.40 6.60 E1 4.70 6.60 e1 4.40 4.60 H 9.35 10.10 L1 2.80 10.10 L2 0.80 1 R 0.20 1	b	0.64		0.90		
c2 0.48 0.60 D 6.00 6.20 D1 5.10 6.60 E 6.40 6.60 E1 4.70 6.60 e1 4.40 4.60 H 9.35 10.10 L1 2.80 1 L2 0.80 1 R 0.20 1	b4	5.20		5.40		
D 6.00 6.20 D1 5.10 6.60 E 6.40 6.60 E1 4.70 6.60 e1 4.40 4.60 H 9.35 10.10 L1 2.80 10.10 L2 0.80 1 R 0.20 1	С	0.45		0.60		
D1 5.10 E 6.40 6.60 E1 4.70 6.60 e 2.28 4.60 e1 4.40 4.60 H 9.35 10.10 L 1 2.80 L1 2.80 1 L2 0.80 1 R 0.20 1	c2	0.48		0.60		
E 6.40 6.60 E1 4.70 6.60 e 2.28 4.60 e1 4.40 4.60 H 9.35 10.10 L 1 2.80 L1 2.80 10.10 L2 0.80 1 R 0.20 1	D	6.00		6.20		
E1 4.70 e 2.28 e1 4.40 H 9.35 L 1 L1 2.80 L2 0.80 L4 0.60 R 0.20	D1		5.10			
e 2.28 e1 4.40 4.60 H 9.35 10.10 L 1 10.10 L1 2.80 10.10 L2 0.80 10.10 L4 0.60 1 R 0.20 1	E	6.40		6.60		
e1 4.40 4.60 H 9.35 10.10 L 1 10.10 L1 2.80 10.10 L2 0.80 1 L4 0.60 1 R 0.20 1	E1		4.70			
H 9.35 10.10 L 1 1 L1 2.80 1 L2 0.80 1 L4 0.60 1 R 0.20 1	е		2.28			
L 1 2.80 L1 2.80 2.80 L2 0.80 1 L4 0.60 1 R 0.20 1	e1	4.40		4.60		
L1 2.80 L2 0.80 L4 0.60 R 0.20	Н	9.35		10.10		
L2 0.80 L4 0.60 1 R 0.20 1	L	1				
L4 0.60 1 R 0.20 1	L1		2.80			
R 0.20	L2		0.80			
	L4	0.60		1		
V2 0 [°] 8 [°]	R		0.20			
	V2	0 °		8 ^o		





4 Revision history

Table 5.Document revision history

Date	Revision	Changes
06-Aug-2009	1	Initial release.



Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

