

Data cable - IFS-MINI-DIN-DATACABLE - 2320487

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Data cable for communication, e.g., between Phoenix Contact type ILC 1xx Inline controllers and Phoenix Contact devices with the 12-pos. IFS data port, such as QUINT UPS-IQ UPS or TRIO UPS

Product description

Data cable for communication between higher level controllers and QUINT UPS-IQ uninterruptible power supply units.

Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 80.0 GRM |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------------------|-----|
| Fixed cable length | 2 m |
|--------------------|-----|

Ambient conditions

| | |
|---|--------------------------------------|
| Ambient temperature (operation) | -25 °C ... 70 °C (-13 °F ... 158 °F) |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C (-40 °F ... 185 °F) |

General

| | |
|---------------------|----------------|
| Connection 1 | Device side |
| Connection method | MINI DIN |
| Number of positions | 6 |
| Note | Serial, RS-232 |
| Connection 2 | Device side |
| Connection method | IFS data port |

Data cable - IFS-MINI-DIN-DATACABLE - 2320487

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27040702 |
| eCl@ss 4.1 | 27040702 |
| eCl@ss 5.0 | 27242213 |
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27049005 |
| eCl@ss 8.0 | 27049005 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001039 |
| ETIM 4.0 | EC000830 |
| ETIM 5.0 | EC000830 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211502 |
| UNSPSC 7.0901 | 39121004 |
| UNSPSC 11 | 39121004 |
| UNSPSC 12.01 | 39121004 |
| UNSPSC 13.2 | 39121004 |