

5900 Series

Tubeaxial

127x127x38mm



- AC fans with external rotor shaded-pole motor. Impedance protected against overloading.
- Metal fan housing, impeller of mineral-reinforced plastic PA.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Mounting from either face using four 4.7 mm holes.
- Electrical connection via 2 flat pins 2.8 x 0.5 mm.
- Fan housing with ground lug for screw M 4x6 DIN 7500-C.
- UL, CSA, VDE approvals on some models, please contact application engineering.
- Available on request:
Electrical connection via 2 single leads.

| Part Number | Curve | CFM @ 0 | VAC | Hertz | Power (W) | dba | Max Amb. Temp C | Bearing Type | Features | Wgt. (lbs) |
|-------------|-------|---------|-----|-------|-----------|-----|-----------------|--------------|-----------|------------|
| 5938 | 2 | 95.3 | 115 | 50/60 | 12 | 39 | 55 | Ball | Terminals | 1.25 |
| 5938-118 | 3 | 105.9 | 115 | 50/60 | 14 | 41 | 65 | Ball | Terminals | 1.25 |
| 5930-507 | 3 | 105.9 | 115 | 50/60 | 14 | 41 | 55 | Sintec | Terminals | 1.25 |
| 5900 | 4 | 121.2 | 115 | 50/60 | 17 | 46 | 55 | Sintec | Terminals | 1.25 |
| 5908 | 4 | 121.2 | 115 | 50/60 | 17 | 47 | 75 | Ball | Terminals | 1.25 |
| 5908W-104 | 4 | 121.2 | 115 | 50/60 | 17 | 47 | 75 | Ball | Leads | 1.25 |
| 5900W-504 | 4 | 121.2 | 115 | 50/60 | 17 | 47 | 75 | Sintec | Leads | 1.25 |
| 5908-105 | 4 | 121.2 | 115 | 50/60 | 17 | 47 | 75 | Ball | Terminals | 1.25 |
| 5900-505 | 4 | 121.2 | 115 | 50/60 | 17 | 47 | 75 | Sintec | Terminals | 1.25 |
| 5988 | 1 | 88.3 | 230 | 50/60 | 12 | 39 | 55 | Ball | Terminals | 1.25 |
| 5950 | 3 | 105.9 | 230 | 50/60 | 17 | 46 | 55 | Sintec | Terminals | 1.25 |
| 5958 | 3 | 105.9 | 230 | 50/60 | 17 | 47 | 60 | Ball | Terminals | 1.25 |
| 5980-508 | 3 | 105.9 | 230 | 50/60 | 14 | 41 | 55 | Sintec | Terminals | 1.25 |
| 5958W-100 | 4 | 121.2 | 230 | 50/60 | 17 | 47 | 75 | Ball | Leads | 1.25 |
| 5950W-502 | 4 | 121.2 | 230 | 50/60 | 17 | 47 | 75 | Sintec | Leads | 1.25 |
| 5950-503 | 4 | 121.2 | 230 | 50/60 | 17 | 47 | 75 | Ball | Terminals | 1.25 |
| 5958-102 | 4 | 121.2 | 230 | 50/60 | 17 | 47 | 75 | Ball | Terminals | 1.25 |

