



3 Type

- A** Mounting from the back (tapped blind hole)
- B** Mounting from the operator's side (only for d1=28)

Specification



- Tube
Aluminum (wall thickness 1.5 mm)
- Handle legs
Zinc die-cast, powder coated
- Tube / handle legs ● **SW**
Powder coated
Black, RAL 9005, textured finish
- Tube ● **EL**
Anodized finish, natural color
Handle legs
Black, RAL 9005, textured finish
- Tube ● **ES**
Anodized finish, natural color
Handle legs
Silver, RAL 9006, textured finish
- Covers
Plastic, light gray
- Cover caps (Type B)
Plastic, Technopolymer
- Black (for SW / EL)
- Light gray (for ES)
- **RoHS compliant**

Information

The handle legs of GN 333 tubular handles are highly stable in relation to their small dimensions. Tube and legs are secured together with self-tapping screws and do not require any further machining or processing steps allowing even small quantities of special lengths to be manufactured. Screw heads are covered with plastic covers to provide a clean and finished look.

Typical use is on double winged swinging doors and sliding doors on machines.

see also...

- *Product Range Standard Parts for Profile Systems*
- *Tubular Handles GN 333.1 (with Straight Legs)*
- *Tubular Handles GN 332 (with Power switching Function)*
- *T-Nut Assemblies GN 965 (for 30 / 40 mm T-Slot Profile Systems)*
- *T-Nut Assemblies GN 968 (for 30 / 40 / 45 mm T-Slot Profile Systems)*

Accessory

- Angled handle legs GN 333.8

On request

- Special tube lengths other than listed

How to order

GN 333-0.79-7.00-A-EL

- 1** Handle diameter d₁
- 2** Length l
- 3** Type
- 4** Finish

Inch table

1 2

Dimensions in: inches - *millimeters*

d ₁	Length l ±0.01							d ₂ Thread	b ₁	b ₂	b ₃	b ₄	h ₁	h ₂	t min.
.79 20.1	7.00 177.8	8.00 203.2	10.00 254.0	12.00 304.8	16.00 406.4	-	1/4 x 20	.94 23.9	.47 11.9	1.65 41.9	2.13 54.1	1.65 41.9	2.13 54.1	.47 11.9	
1.10 27.9	8.00 203.2	10.00 254.0	12.00 304.8	16.00 406.4	20.00 508.0	24.00 609.6	5/16 x 18	.98 24.9	.55 14.0	1.97 50.0	2.60 66.0	1.97 50.0	2.60 66.0	.59 15.0	

Metric table

1 2

Dimensions in: millimeters - *inches*

d ₁	Length l ±0.25							d ₂ Thread	b ₁	b ₂	b ₃	b ₄	h ₁	h ₂	t min.
20 .79	180 7.09	200 7.87	250 9.84	300 11.81	350 13.78	400 15.75	-	M 6	24 .94	12 .47	42 1.65	54 2.13	42 1.65	54 2.13	12 .47
28 1.10	200 7.87	250 9.84	300 11.81	350 13.78	400 15.75	500 19.69	600 23.62	M 8	25 .98	14 .55	50 1.97	66 2.60	50 1.97	66 2.60	15 .59
30 1.18	200 7.87	300 11.81	350 13.78	400 15.75	500 19.69	600 23.62	1000 39.37	M 8	27 1.06	17 .67	51 2.01	68 2.68	51 2.01	68 2.68	15 .59

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

