

In case of consideration for using Autom otive equipm ent/device which dem and high reliability, kindly contactour sales w indow correspondents.

APPLICABLE STANDARD		OPERATING TEMPERATURE RANGE		STORAGE TEMPERATURE RANGE	
RATING		-30°C TO + 85°C (NOTE 1)		-10°C TO + 60°C (NOTE 2)	
OPERATING HUMIDITY RANGE		40% TO 80% (NOTE 3)		40% TO 70% (NOTE 2)	
VOLTAGE		AC 250V		UL - CSA VOLTAGE	
CURRENT		2A		RATING CURRENT	
				AC 30V	
				2A	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS			
CONSTRUCTION		GENERAL EXAMINATION			
MARKING		VISUALLY AND BY MEASURING INSTRUMENT.		CONFIRMED VISUALLY.	
ELECTRIC CHARACTERISTICS		CONTACT RESISTANCE			
INSULATION RESISTANCE		500V DC.		1000MΩ MIN.	
VOLTAGE PROOF		650V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.	
MECHANICAL CHARACTERISTICS		MECHANICAL OPERATION			
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. OF PARTS.	
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. OF PARTS.	
ENVIRONMENTAL CHARACTERISTICS		DAMP HEAT (STEADY STATE)			
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → 5 TO 35 → +85 → 5 TO 35°C TIME 30 → 5MAX → 30 → 5MAX min UNDER 5 CYCLES.		① CONTACT RESISTANCE: 30mΩ MAX. ② INSULATION RESISTANCE: 500MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	
RESISTANCE TO SOLDERING HEAT		1)AUTOMATIC SOLDERING (FLOW) SOLDER TEMPERATURE : 260°C FOR IMMERSION,DURATION , 10 sec . 2)MANUAL SOLDERING SOLDERING IRON TEMPERATURE : 300°C SOLDERING TIME : 2 sec. NO STRENGTH ON CONTACT.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, 230°C FOR INSERTION DURATION, 3sec.		SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△					
REMARKS					
NOTE 1:INCLUDING THE TEMPERATURE RISE BY CURRENT AFTER PCB BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.					
NOTE2:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD.					
NOTE3:NON-CONDENSING.					
Unless otherwise specified , refer to JIS C 5402.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-020817-02	
HRS SPECIFICATION SHEET		PART NO.	DF11-8DP-2DSA (08)		
HIROSE ELECTRIC CO., LTD.		CODE NO.	CL543-0519-0-08		
				△	1/1