



Key-operated switch O.M.R, 22 mm, round, metal, shiny, lock number 73038, blue, with 2 keys, 3 switch positions I-O-II, latching, actuating angle 2x45°, 10:30h/12h/13:30h, Key removal I+O+II, Z=50-unit packaging

|   |  |
|---|--|
| <b>product brand name</b>                                 | SIRIUS ACT                             |
| <b>product designation</b>                                | Key-operated switches                  |
| <b>design of the product</b>                              | Actuating/signaling element            |
| <b>product type designation</b>                           | 3SU1                                   |
| <b>product line</b>                                       | Metal, shiny, 22 mm                    |
| <b>manufacturer's article number of included key</b>      | <a href="#">3SU1950-0FJ50-0AA0</a>     |
| <b>Actuator</b>   |  |
| <b>principle of operation of the actuating element</b>    | latching, 2x45° (10:30 h/12 h/13:30 h) |
| <b>product extension optional light source</b>            | No                                     |
| <b>color</b>  |  |
| • of the actuating element                                | blue                                   |
| <b>material of the actuating element</b>                  | metal                                  |
| <b>shape of the actuating element</b>                     | Key                                    |
| <b>outer diameter of the actuating element</b>            | 29.5 mm                                |
| <b>number of switching positions</b>                      | 3                                      |
| <b>switch position for key distraction</b>                | O+I+II                                 |
| <b>actuating angle</b>                                    |  |
| • clockwise   | 45°                                    |
| • anticlockwise   | 45°                                    |
| <b>lock make</b>  | O.M.R.                                 |
| <b>key number</b>   | 73038                                  |
| <b>Front ring</b>   |  |
| <b>product component front ring</b>                       | Yes                                    |
| <b>design of the front ring</b>                           | Standard                               |
| <b>material of the front ring</b>                         | Metal, high gloss                      |
| <b>color of the front ring</b>                            | silver                                 |
| <b>General technical data</b>                             |  |
| <b>protection class IP</b>                                | IP66, IP67, IP69(IP69K)                |
| • of the terminal   | IP20                                   |
| <b>degree of protection NEMA rating</b>                   | 1, 2, 3, 3R, 4, 4X, 12, 13             |
| <b>shock resistance</b>                                   |  |
| • according to IEC 60068-2-27                             | sinusoidal half-wave 15g / 11 ms       |
| <b>vibration resistance</b>                               |  |
| • according to IEC 60068-2-6                              | 10 ... 500 Hz: 5g                      |
| <b>operating frequency maximum</b>                        | 1 800 1/h                              |
| <b>mechanical service life (switching cycles) typical</b> | 300 000                                |
| <b>reference code according to IEC 81346-2</b>            | S                                      |
| <b>Substance Prohibitance (Date)</b>                      | 10/01/2014                             |
| <b>Ambient conditions</b>                                 |  |

|  |  |
|--|--|
| <b>ambient temperature</b>   |  |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul> | <p>-25 ... +70 °C</p> <p>-40 ... +80 °C</p>                        |
| environmental category during operation according to IEC 60721                             | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |

#### Installation/ mounting/ dimensions

|  |         |
|--|---------|
| <b>height</b>                                      | 29.5 mm |
| <b>width</b>                                       | 29.5 mm |
| <b>shape of the installation opening</b>           | round   |
| <b>mounting diameter</b>                           | 22.3 mm |
| <b>positive tolerance of installation diameter</b> | 0.4 mm  |
| <b>mounting height</b>                             | 51.7 mm |
| <b>installation width</b>                          | 29.5 mm |
| <b>installation depth</b>                          | 25.4 mm |

#### Certificates/ approvals

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-4GL11-0AA0-Z X90>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-4GL11-0AA0-Z X90>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-4GL11-0AA0-Z X90>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1050-4GL11-0AA0-Z X90&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-4GL11-0AA0-Z X90&lang=en)

last modified:

1/26/2022 