

**Surge protection  
SPD II 1 R 400V/50KA**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Surge protection for use in low-voltage supplies. The SPD II series is tested according to UL 1449 ed. 3 (file E354261) as type 4 for use in type 2 applications. These arresters are used in mains voltages up to 385 V L-PEN, installed according to the mains system specifications and are able to discharge a rated current of up to 50 kA (8/20  $\mu$ s) per path. The SPD II has a compact, modular structure and a standard module width of 17.8 mm; it allows rapid and simple exchange of the arrester. This spare arrester allows re-activation of the SPD II 385 V protection after failure.

**General ordering data**

Order No.	<a href="#">1348430000</a>
Type	SPD II 1 R 400V/50KA
Version	Surge protection, Low voltage, with telecomm. contact
GTIN (EAN)	4050118152791
Qty.	1 pc(s).

**Surge protection  
SPD II 1 R 400V/50KA**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Width	18 mm	Height	100 mm
Depth	73.5 mm	Net weight	150 g

**Temperatures**

Operating temperature	-40 °C...+70 °C	Storage temperature	-40 °C...+85 °C
-----------------------	-----------------	---------------------	-----------------

**General data**

Colour	Light Grey	Design	Installation housing; 1TE
Height with TS 35	74 mm	Lightning arrester	No
Mounting rail	TS 35, TS 35 x 15, TS 35 x 7.5	Optical function display	green = OK; red = arrester is defective - replace
Protection degree	IP 20	UL 94 flammability rating	V-0

**Insulation coordination acc. to EN 50178**

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

**technical data**

Rated voltage (AC)	347 V	Highest continuous voltage (AC)	385 V
Short-circuit current rating $I_{SCCR}$	200 kA	Total discharge current $I_{total}$	50 kA
Discharge current, max. (8/20 $\mu$ s)	50 kA	Protection level $U_p$ (typ.)	$\leq 1800$ V
Signalling contact	250 V / 0,5 A, 48 VDC / 0,1 A	Colour	Light Grey
AC/DC/UC	AC	Response time	$\leq 100$ ns

**Connection data**

Clamping range, rated connection	25 mm <sup>2</sup>	Clamping range, rated connection, min.	4 mm <sup>2</sup>
Clamping range, rated connection, max.	35 mm <sup>2</sup>	Wire connection cross section, stranded, rated connection, min.	2.5 mm <sup>2</sup>
Wire connection cross section, stranded, rated connection, max.	25 mm <sup>2</sup>	Tightening torque, min.	2.5 Nm
Tightening torque, max.	3.5 Nm	Stripping length, rated connection	15 mm

**Connection data, remote alert**

Connection type [remote alert]	Screw connection	Max. torque [remote alert]	0.22 Nm
Stripping length [remote alert]	5 mm	Cross-section for connected wire, solid core, min. [remote alert]	0.2 mm <sup>2</sup>
Cross-section for connected wire, solid core, max. [remote alert]	1.5 mm <sup>2</sup>		

**Rated data UL**

Category	Typ 2	$I_{max}$	50 kA
$I_n$	20 kA	MCOV	385 Vac
SCCR	200 kA	Test Voltage 39.1 (UL 1449)	600 V
UL certificate	E-File 354261 Type 2 by UL1449 Ed.3	VPR	1.8 kV

**Surge protection  
SPD II 1 R 400V/50KA**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Classifications**

ETIM 3.0	EC000941	UNSPSC	30-21-19-21
eClass 5.1	27-13-08-01	eClass 6.2	27-13-08-02
eClass 7.1	27-14-02-01		

**Approvals**

Approvals



ROHS Conform

**Downloads**

Declaration of Conformity	<a href="#">K481_05_12.pdf</a>
EPLAN	<a href="#">1348430000.ema</a>

**Surge protection  
SPD II 1 R 400V/50KA**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings**

**Electric symbol**

