



Scan the QR code and  
visit the product page



Code	TK.LB.D0260.AEC	Safety level	Danger
Dimensions (H x L)	69 mm x 140 mm (2,7" x 5,5")	Version	Standard
Material	PVC base with adhesive liner and protective layer	Temperatures <sup>(1)</sup>	-40°C/+95°C
Applications	Machinery and control panels. Indoor and outdoor locations		
Languages <sup>(2)</sup>	Inglese		
Message <sup>(3)</sup>	EN: Hazardous voltage. Multiple power sources may be present. Lockout/tagout before servicing. IT: Tensione pericolosa. Potrebbero essere presenti più sorgenti di alimentazione. Blocco e identifica prima della manutenzione.		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286		
Standards Construction	ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	12 pz/pcs		

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.