



Main

Range	Spacial
Product name	Spacial SMX
Enclosure type	Computer protection PC application
Category	Compact enclosure
Nominal height	62.99 in (1600 mm)
Nominal width	23.62 in (600 mm)
Nominal depth	23.62 in (600 mm)
Product installation	Floor-standing
Device composition	1 body 1 cable gland plate 1 partial door for keyboard 1 partial door for PC screen 1 partial door for printer support/CPU 1 rear door

Complementary

Body type	Single piece body folded and welded
Door type	Glazed partial Plain partial Solid
Door opening side	Reversible 120 °)
Number of doors	Front 2 Front 1 Rear 1
Lock type	3 mm double-bar lock
Type of gland plate	Plain
Accessibility for operation	Rear Front
Mounting plate description	Without mounting plate
Material	Body and door stainless steel 304L Hinge stainless steel Door Securit glass Lock zamak
Removable parts	Cable gland plate by clips Door by hinges rear Partial doors by hinges front Transparent shutter by screws
Surface finish	Body and door micro beaded Securit glass silkscreened Lock chromium plated
Net Weight	220.46 lb(US) (100 kg)

Environment

Standards	IEC 62208
IP degree of protection	IP55 IEC 60529 even with the keyboard drawer open)
IK degree of protection	IK10 IEC 62262 plain door) IK08 IEC 62262 glazed door)
Environmental characteristic	Specific hygiene Corrosive

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480155727
Nbr. of units in pkg.	1
Package weight(Lbs)	229.28 lb(US) (104.0 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	31.50 in (80.0 cm)
Package 1 width	31.50 in (80.0 cm)
Package 1 Length	70.87 in (180.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------