

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT 2006 By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00	P	REVISED PER ECO-11-004835	11MAR11	RK HMR

.256 DIA MAX

CABLE SUPPORT HOUSING

45°

SHIM

GATE SCREW (BLACK)

CABLE SUPPORT GATE

CROSS RECESSED PAN HEAD, SELF TAPPING SCREW

(1.775)

(1.625)

AMP

SIZE #1 PLUG OR RECEPTACLE REF ONLY

.750

.805 MAX

.640 MAX

1. PARTS PACKAGED UNASSEMBLED.

2 COMPONENTS INDIVIDUALLY BULK PACKED & SHIPPED AS A UNIT PACKAGE KIT.

3 MOLDED PARTS: POLYPROPYLENE, BLACK  
SHIM: BRASS  
SCREWS: COLD ROLLED STEEL

4 GATE SCREWS: BLACK ZINC PHOSPHATE, SELF-TAPPING SCREWS: ZINC PLATED CLEAR CHROMATE COATING.

COMBINATION DRIVE	2	5205729-3
COMBINATION DRIVE	AS SHOWN	5205729-1
SCREW VERSION	PACKAGING	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R.RICHARDSON 22AUG05		
DIMENSIONS: INCHES		CHK C. ROHDE 22AUG 05		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M.WALMSLEY 22AUG05	NAME	
0 PLC ± -		PRODUCT SPEC	SELF TAPPED 45/180 DEG	
1 PLC ± -		APPLICATION SPEC	CABLE SUPPORT CLAMSHELL, SIZE 1	
2 PLC ± -		WEIGHT	ASSEMBLY, AMPLIMITE HD-20	
3 PLC ± .005		SIZE	CAGE CODE	DRAWING NO
4 PLC ± -		A2	00779	C=5205729
ANGLES ± -		SCALE 4:1		SHEET 1 of 1
FINISH		CUSTOMER DRAWING		REV P

1471-9 (3/11)

5205729