


- 20 POSITION CONNECTOR ASSEMBLY SHOWN.
- MOLDED PARTS: THERMOPLASTIC, UL94V-0 RATED, COLOR BLUE. CONTACTS: BERYLLIUM COPPER.
- CONTACTS: 0.00076[.000030] MIN GOLD ON MATING AREA, 0.00254-0.00508[.000100-.000200] BRIGHT TIN LEAD ON TERMINATION END, ALL OVER 0.00127[.000050] MIN NICKEL ON ENTIRE CONTACT.
- POLARIZER FEATURE DOES NOT EXIST ON POSITION #1 END FOR 14 POSITION ASSEMBLIES AND SMALLER.
- POLARIZER FEATURE DOES NOT EXIST ON THIS END FOR 4 & 6 POSITION ASSEMBLIES.
- FOR TERMINATION OF 26 OR 28 AWG STRANDED OR SOLID PVC INSULATED FLAT RIBBON CABLE. SEE TYCO DRAWINGS 57034 (26 AWG) OR 57040 (28 AWG) FOR DETAILS.
- STRAIN RELIEF PACKAGED SEPARATELY AND SHIPPED WITH ASSEMBLY.



YES	YES	3.80[.150]	85.78[3.377]	80.01[3.150]	78.74[3.100]	64	622-6441	4-1437025-3
NO	YES	3.80[.150]	85.78[3.377]	80.01[3.150]	78.74[3.100]	64	622-6430	3-1437025-7
YES	YES	3.80[.150]	80.70[3.177]	74.93[2.950]	73.66[2.900]	60	622-6041	3-1437025-2
NO	YES	3.80[.150]	80.70[3.177]	74.93[2.950]	73.66[2.900]	60	622-6030	2-1437025-7
NO	YES	3.80[.150]	75.62[2.977]	69.85[2.750]	68.58[2.700]	56	622-5630	2-1437022-9
YES	YES	3.80[.150]	68.00[2.677]	62.23[2.450]	60.95[2.400]	50	622-5041	1-1437025-6
NO	YES	3.80[.150]	68.00[2.677]	62.23[2.450]	60.95[2.400]	50	622-5030	1437025-4
NO	NO	-	60.38[2.377]	54.61[2.150]	53.34[2.100]	44	622-4400	2-1437022-1
YES	YES	3.80[.150]	55.30[2.177]	49.53[1.950]	48.26[1.900]	40	622-4041	8-1437024-6
NO	YES	3.80[.150]	55.30[2.177]	49.53[1.950]	48.26[1.900]	40	622-4030	7-1437024-7
YES	YES	3.80[.150]	47.68[1.877]	41.91[1.650]	40.64[1.600]	34	622-3441	5-1437024-6
NO	YES	3.80[.150]	47.68[1.877]	41.91[1.650]	40.64[1.600]	34	622-3430	4-1437024-8
YES	YES	3.80[.150]	42.60[1.677]	36.83[1.450]	35.56[1.400]	30	622-3041	4-1437024-1
NO	YES	3.80[.150]	42.60[1.677]	36.83[1.450]	35.56[1.400]	30	622-3030	3-1437024-8
YES	YES	3.80[.150]	37.52[1.477]	31.75[1.250]	30.48[1.200]	26	622-2641	3-1437024-0
NO	YES	3.80[.150]	37.52[1.477]	31.75[1.250]	30.48[1.200]	26	622-2630	2-1437024-4
YES	YES	3.80[.150]	34.98[1.377]	29.21[1.150]	27.94[1.100]	24	622-2441	2-1437024-7
NO	YES	3.80[.150]	34.98[1.377]	29.21[1.150]	27.94[1.100]	24	622-2430	1-1437024-4
YES	YES	3.80[.150]	29.90[1.177]	24.13[.950]	22.86[.900]	20	622-2041	1437024-7
NO	YES	3.80[.150]	29.90[1.177]	24.13[.950]	22.86[.900]	20	622-2030	1437024-2
YES	YES	3.80[.150]	24.82[.977]	19.05[.750]	17.78[.700]	16	622-1641	9-1437023-1
NO	YES	3.80[.150]	24.82[.977]	19.05[.750]	17.78[.700]	16	622-1630	8-1437023-3
YES	YES	3.80[.150]	22.28[.877]	16.51[.650]	15.24[.600]	14	622-1441	7-1437023-4
NO	YES	3.80[.150]	22.28[.877]	16.51[.650]	15.24[.600]	14	622-1430	6-1437023-6
YES	YES	3.80[.150]	19.74[.777]	13.97[.550]	12.70[.500]	12	622-1241	5-1437023-9
NO	YES	3.80[.150]	19.74[.777]	13.97[.550]	12.70[.500]	12	622-1230	5-1437023-7
YES	YES	3.20[.126]	17.20[.677]	11.43[.450]	10.16[.400]	10	622-1041	4-1437023-9
NO	YES	3.20[.126]	17.20[.677]	11.43[.450]	10.16[.400]	10	622-1030	4-1437023-1
NO	NO	-	14.66[.577]	8.89[.350]	7.62[.300]	8	622-0800	1-1437022-7
YES	YES	1.90[.075]	12.12[.477]	6.35[.250]	5.08[.200]	6	622-0641	3-1437023-1
NO	YES	1.90[.075]	12.12[.477]	6.35[.250]	5.08[.200]	6	622-0630	2-1437023-6
NO	YES	1.90[.075]	9.58[.377]	3.81[.150]	2.54[.100]	4	622-0430	1-1437023-8
STRAIN RELIEF	CENTER POLARIZER	D	C	B	A	NUMBER OF POSITIONS	T&B PART NUMBER (REFERENCE)	TYCO PART NUMBER

ELECTRICAL PROPERTIES	
CURRENT RATING	1 AMP
INSULATION RESISTANCE	>1 x 10 ⁹ OHMS @ 500 VDC
DWV	>500 VRMS AT SEA LEVEL
ENVIRONMENTAL PROPERTIES	
TEMPERATURE RATING	-55°C TO 125°C

**COPYRIGHT 2004
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± 0.13[.005]	4 PLC ± -	ANGLES ± -	FINISH
--------------------	--	-----------	-----------	-----------	--------------------	-----------	------------	--------

DWN: J. GERACE 19AUG04
 CHK: C. ROHDE 19AUG04
 APVD: M. WALMSLEY 19AUG04
 NAME: M. WALMSLEY
 PRODUCT SPEC: CONNECTOR ASSEMBLY, FEMALE SOCKET TRANSITION, 622 SERIES
 APPLICATION SPEC: -
 SIZE: A1
 CASE CODE: 00779
 DRAWING NO: 2-1437022-9
 RESTRICTED TO: -
 WEIGHT: -
 CUSTOMER DRAWING: -
 SCALE: 10:1
 SHEET: 1 OF 1
 REV: 0