TGBWP, T and BMT Series



TGBWP Series



1-1/8"-18 thread; trunk/hood groove bracket mount

STANDARD CONFIGURATION						
Model	Length of Coax	Coax	Connector*	Cable Exit Angle	Туре	
TGBWP45C-NC	17′	RG-58/U	None	45°	N/A	
TGBWP45PL	17′	RG-58/U	Mini-UHF	45°	Crimp	
TGBWP45FFME	17′	RG-58/U	Female FME*	45°	Crimp	



TGBWP45

T Series

1-1/8"-18 thread mount; trunk lid mount

STANDARD CONFIGURATION

Model	Length of Coax	Coax	Connector*	Туре
TTT	NA	None	None	N/A
T-NC	17′	RG-58A/U	None	N/A
TC-NC	17′	RG-58/U	None	N/A
T	17'	RG-58A/U	PL259	Solder
TC	17′	RG-58/U	TNC	Crimp
TPL	17′	RG-58/U	Mini-UHF	Crimp



BMT Series

Black 1-1/8"-18 thread; all metal trunk lid mount; 17' RG-58/U or RG-58A//U cable options. For other cable lengths and connector configuration options, contact PCTEL Customer Service.



BMT

^{*} Connectors are shipped loose. Connectors may be attached upon request for an additional charge. For other connector options, please refer to the Mobile Antenna Mounts Configurator Part Number Guide.