

## Screw termination block - CT-TERMIBLOCK 10 DA - 0441711

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Screw termination block with disconnect contacts for accommodating protective plugs CT and CTM. Use in MCR and telecommunications systems. Design: 10 double wires

### Why buy this product

- For COMTRAB protective plugs
- Automatically closing feed-through/disconnect contacts
- Ground terminal blocks on both sides with plug-in connection for the protective plugs used
- Mounting on DIN rails according to EN 60715



### Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 123 (TT-2011)
GTIN	 4 017918 002213
Custom tariff number	85369010
Country of origin	GERMANY

### Technical data

#### General

Housing material	PA
Inflammability class according to UL 94	V2
Color	black
Standards for air and creepage distances	IEC 60664-1
Surge voltage category	III
Pollution degree	3
Ambient temperature (operation)	-40 °C ... 85 °C
Mounting type	NS 32/NS 35
Design	LSA-PLUS module
Degree of protection	IP20
Width	118 mm
Height	43 mm

# Screw termination block - CT-TERMIBLOCK 10 DA - 0441711

## Technical data

### General

Depth	40.9 mm
-------	---------

### Protective circuit

Maximum continuous voltage UC (wire-wire)	240 V AC
Maximum continuous voltage UC (wire-ground)	250 V AC
Operating effective current IC at UC	5 A

### Connection data

Connection method	Screw terminal blocks
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	7 mm
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	14

## Classifications

### eclass

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807

### etim

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943

### unspsc

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

# Screw termination block - CT-TERMIBLOCK 10 DA - 0441711

## Approvals

Approvals

---

Approvals

UL Recognized / GOST / UL Listed

---


Ex Approvals

---

Approvals submitted

---

## Approval details

UL Recognized 

GOST 

UL Listed 

## Drawings

Dimensioned drawing

