

**Data sheet | Item number: 745-384**

Jumper; 4-way; unplated; silver-colored

[www.wago.com/745-384](http://www.wago.com/745-384)



## Data

### Electrical data

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



## Ratings per IEC/EN

Rated current	41 A
---------------	------

## Physical data

Pin spacing	7.5 mm / 0.295 inches
Jumper assignment	1-2-3-4

## Mechanical Data

Suitable	for 745 Series (6 mm <sup>2</sup> ) and 2706 Series
----------	---

## Material Data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
----------------------	--

Color	silver-colored
Contact material	Copper alloy
Contact plating	Tin
Weight	3.6 g

## Commercial data

Product Group	4 (Printed Circuit Connectors)
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-44-04-92
ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	200 (50) pcs
Packaging type	box
Country of origin	CH
GTIN	4017332608428
Customs tariff number	85366990990

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Downloads

### Documentation

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.

Additional Information

2019 年4月3日

pdf  
2.0 MB

Download

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 745-384

URL


Download

Jumper; 4-way; unplated; silver-colored

Installation Notes



Inserting a comb-style jumper bar.



To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.



To remove the jumper bar, lift it up using a screwdriver – 745 Series.

Subject to changes. Please also observe the further product documentation!