

#### VAL-U-LOK

TE Internal #: 1586861-6 Rectangular Power Connectors, Housing, Plug, Wire-to-Panel / Wire-to-Wire, 6 Position, 4.2 mm [.165 in] Centerline, Wire & Cable, UL 94V-2

#### View on TE.com >

#### Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug

Connector System: Wire-to-Panel, Wire-to-Wire

Number of Positions: 6

Centerline (Pitch): 4.2 mm [.165 in ]

# Features

**E** 

#### **Product Type Features**

Rectangular Power Connector Type	Housing			
Connector & Housing Type	Plug			
Connector System	Wire-to-Panel, Wire-to-Wire			
Sealable	No			
Connector & Contact Terminates To	Wire & Cable			
Configuration Features				
Insertion Force	15 Newton			
Compatible With Wire & Cable Type	Discrete Wire			
Number of Positions	6			
Number of Power Positions	0			
Number of Signal Positions	0			
Number of Rows	2			
Electrical Characteristics				
Operating Voltage	600 VAC			

Rectangular Power Connectors, Housing, Plug, Wire-to-Panel / Wire-to-Wire, 6 Position, 4.2 mm [.165 in] Centerline, Wire & Cable, UL 94V-2



### **Contact Features**

Contact Layout	Matrix
Contact Retention Within Housing	Without
Contact Type	Pin
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	4.2 mm[.165 in]
Housing Color	White
Housing Material	Polyamide
Dimensions	
Connector Height	9.6 mm[.378 in]
Product Width	23.9 mm[.94 in]
Product Length	13.8 mm[.543 in]
Compatible Insulation Diameter Range	1.2 – 3.1 mm[.047 – .122 in]
Row-to-Row Spacing	4.2 mm[.165 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Identification Marking	
Circuit Identification Feature	With
Industry Standards	
CSA Rating	208567
UL Rating	Recognized
Agency/Standard	CSA, UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-2
Glow Wire Rating	GWT 750°C (Without Flame)

Rectangular Power Connectors, Housing, Plug, Wire-to-Panel / Wire-to-Wire, 6 Position, 4.2 mm [.165 in] Centerline, Wire & Cable, UL 94V-2



#### Packaging Features

Packaging Quantity	500
Packaging Method	Bag

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC	
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.	
Solder Process Capability	Not applicable for solder process capability	

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



Rectangular Power Connectors, Housing, Plug, Wire-to-Panel / Wire-to-Wire, 6 Position, 4.2 mm [.165 in] Centerline, Wire & Cable, UL 94V-2





# Customers Also Bought



7 POS EP 2.5 HSG, GLOW WIRE	CLIP 6.35 MM SECUR	VAL-U-LOK PIN BR SN 18-22AWC	MONO-SHAPE MK I TAB CONN ASSY



# Documents

Product Drawings 6P PM PLUG VAL-U-LOK PM GW

English

#### **CAD** Files

Customer View Model ENG\_CVM\_CVM\_1586861-6\_B.2d\_dxf.zip

English

3D PDF

**C** For support call+1 800 522 6752

Rectangular Power Connectors, Housing, Plug, Wire-to-Panel / Wire-to-Wire, 6 Position, 4.2 mm [.165 in] Centerline, Wire & Cable, UL 94V-2



3D

Customer View Model ENG\_CVM\_CVM\_1586861-6\_B.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1586861-6\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages VAL-U-LOK\_GLOW\_WIRE\_CONNECTORS

English

Product Specifications Application Specification

English

Agency Approvals UL Report

English