18 INCHES LENGTH



Connector A 901-9872 SMA Plug Right Angle Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 142233 SMB Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector B	Connector A			Cable			Connector B		
135° 45° 180° 225' 270° 220° 315' Connector A	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	901-9872 SMA R/A PLUG I SMA Plug Right Angle Solder Standard 50 Ohm Cable Brass Gold None Brass Gold 12.4 GHz SMA Plug Right <i>i</i>		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 18 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	142233 SMB R/A BHD JK R 50O SMB Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mc Brass Gold None Brass Gold 4 GHz SMB Jack Right Ang 0°		
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CODV			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE V CUSTOM CABLE INC. ACCEPTA ESTABLISHES AND AGREEMEN	AND MUST NOT BE U TAL TO CUSTOM CA ICED OR TRANSCRIB WRITTEN CONSENT O ANCE OF THIS DRAW	BLE ED F ING Part No:	SMA-RA-PL/SMB-RA-JK G174 18I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	