

DEUTSCH | DEUTSCH DT, DEUTSCH DTP

TE Internal #: DTP04-4P-LE07

Housing for Male Terminals, Wire-to-Wire, 4 Position, .264 in [6.71 mm] Centerline, Sealable, Gray, Wire & Cable, Power & Signal,

Panel Mount, Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DTP Housings



Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 2.39 mm [.094 in]

Connector System: Wire-to-Wire

Number of Positions: 4

Centerline (Pitch): 6.71 mm [.264 in]

All DEUTSCH DTP Housings (34)

Features

Product Type Features

| Connector Shape | Rectangular |
|-----------------------------------|----------------------------|
| Connector & Housing Type | Housing for Male Terminals |
| Connector System | Wire-to-Wire |
| Sealable | Yes |
| Hybrid Connector | No |
| Primary Locking Feature | Integrated in Housing |
| Connector & Contact Terminates To | Wire & Cable |

Configuration Features

| Blank Cavity Position | 0 |
|------------------------|------------------------|
| Connector Modification | Welded Flange, End Cap |
| Number of Positions | 4 |
| Number of Rows | 2 |

Electrical Characteristics

| Operating Voltage | 200 VAC |
|------------------------------|------------------|
| Nominal Voltage Architecture | 12 V, 24 V, 48 V |

Body Features



| Cable Exit Angle | 180° |
|--------------------------------------|------------------------------------|
| Primary Product Color | Gray |
| Contact Features | |
| Contact Size | Size 12 |
| Contact Type | Pin |
| Mating Pin Diameter | 2.39 mm[.094 in] |
| Contact Current Rating (Max) | 25 A |
| Mechanical Attachment | |
| Terminal Position Assurance | Yes |
| Strain Relief | Add By Accessory |
| Mating Alignment Type | Polarized |
| Mating Alignment | With |
| Connector Mounting Type | Panel Mount |
| Housing Features | |
| Housing Material | PA GF |
| Centerline (Pitch) | 6.71 mm[.264 in] |
| Dimensions | |
| Connector Height | 38.1 mm[1.5 in] |
| Product Width | 53.34 mm[2.1 in] |
| Product Length | 49.05 mm[1.931 in] |
| Row-to-Row Spacing | 10.16 mm[.4 in] |
| Compatible Insulation Diameter Range | 3.4 – 4.32 mm[.134 – .17 in] |
| Usage Conditions | |
| Operating Temperature (Max) | 125 °C[257 °F] |
| Operating Temperature Range | -55 – 125 °C[-67 – 257 °F] |
| Operation/Application | |
| Circuit Application | Power & Signal |
| Industry Standards | |
| Degree of Protection | IP68 |
| Agency/Standard | SAE J2030 |
| UL Flammability Rating | 20mm Flame Test per Standard UL-94 |
| | |

Packaging Features



| Packaging Quantity | 200 |
|--------------------------------------|-----|
| Packaging Method | Box |
| Other | |
| Serviceable | Yes |
| Connector Position Assurance Capable | No |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.5% in Component Part) Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-D48-SP729
DEUTSCH Sealing Plugs



TE Part # CAT-D486-CH8172
DEUTSCH DTP Housings



TE Part # CAT-D48-ST273
DEUTSCH Solid Contacts



TE Part # WP-4P WEDGE LOCK, 4P, REC, ORG, DTP



TE Part # DT-RT1

EXT TOOL, FRONT RELEASE



TE Part # 1011-118-0405 SEAL RET, 4P, GRY, DTP



TE Part # DTP4P-L012-GKT GASKET, 4P, BLK, DTP



TE Part # 1060-12-0144 PIN, SF, SIZE 12, 12-14, AU/SN



TE Part # 1060-12-0222 PIN, SF, SIZE 12, 10, NI/NI



TE Part # 1060-12-0166 PIN, SF, SIZE 12, 12-14, NI/SN



Also in the Series | DEUTSCH DT



Automotive Connector Caps & Covers (107)



Automotive Connector Locks & Position Assurance(74)



Automotive Housings(618)



Connector Seals & Cavity Plugs(6)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(27)



PCB Headers & Receptacles(103)

Also in the Series | DEUTSCH DTP





Automotive Connector Caps & Covers (1)




Automotive Connector Locks & Position Assurance(4)



Automotive Housings(34)



Insertion & Extraction Tools(3)



PCB Headers & Receptacles(4)

Customers Also Bought



TE Part #DT06-3S-CP01
DEUTSCH DT Plug Connectors



TE Part #WP-4P
WEDGE LOCK, 4P, REC, ORG, DTP



TE Part #DT04-12PA-LE09
DEUTSCH DT Receptacle Connectors



TE Part #DTP06-4S-E003 PLG, 4P, GRY, N, CAP



TE Part #DTP4P-L012-GKT GASKET, 4P, BLK, DTP



TE Part #DTV06-18SA PLG, 18P, GRY, N, A



Documents

Product Drawings

REC, 4P, GRY, N, CAP, FLANGE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DTP04-4P-LE07_B.2d_dxf.zip

Housing for Male Terminals, Wire-to-Wire, 4 Position, .264 in [6.71 mm] Centerline, Sealable, Gray, Wire & Cable, Power & Signal, Panel Mount, Hybrid



English

Customer View Model

ENG_CVM_CVM_DTP04-4P-LE07_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DTP04-4P-LE07_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English