

Accessories - MCC-MT 0,2-0,35 - 1859988

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Female contact, is inserted into the plug after crimping the conductor, for the module plug housing MCC 1...-STZ-3,81 and MCC 1...-STZF-3,81, for cross sections of 0.2 mm² to 0.34 mm²



Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 851 (CC-2011)
GTIN	 4 017918 109721
Custom tariff number	85366990
Country of origin	GERMANY

Technical data

Technical data

Nominal current	4 A
Conductor cross section stranded min.	0.2 mm ²
Max. conductor cross section, stranded	0.35 mm ²

Connection data

Core diameter including insulation	0.13 mm ... 0.2 mm
Stripping length of individual wires	4 mm

Classifications

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC001121

UNSPSC

UNSPSC 11	39121409
UNSPSC 12.01	39121409

Accessories - MCC-MT 0,2-0,35 - 1859988

Classifications

UNSPSC

UNSPSC 13.2	39121409
UNSPSC 6.01	30211810
UNSPSC 7.0901	39121410

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details

GOST 
--

Drawings

Accessories - MCC-MT 0,2-0,35 - 1859988

Dimensioned drawing



