

00 30 524 0440

Han 24B-HTE-R-NPTF 3/4 Zoll

	Part number 09 30 524 0440	
	Specification Han 24B-HTE-R-NPTF	3/4 Zoll
Identification		
Category	Hoods/Housings	
Series of hoods/housings	Han [®] B	
Type of hood/housing	Hood	
Туре	High construction	
Version		
Size	24 B	
Version	Top entry	
Cable entry	1x NPTF 3/4"	
Locking type	Single locking lever	
Field of application	Standard hoods/housings for industrial connectors	
Technical characteristics		

Part number

Technical characteristics

Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65 IP66 IP67

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
RoHS	compliant
ELV status	compliant

Page 1 / 2 | Creation date 2023-06-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R1 (HL 1-3) R7 (HL 1-3)

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes
Approvals	DNV GL
Commercial data	
Packaging size	1
Net weight	255 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors