



CORE DIMENSIONS					
UNCOATED CORE			35T0155-200		
	MM	INCHES		MM	INCHES
OD	3.94	(.155)	±	.13	(.005)
ID	2.24	(.088)	±	.13	(.005)
TH	2.01	(.079)	±	.13	(.005)
PARYLENE			35T0155-20P		
OD	3.96	(.156)	±	.13	(.005)
ID	2.21	(.087)	±	.13	(.005)
TH	2.03	(.080)	±	.13	(.005)

INITIAL PERMEABILITY 5000  
 WEIGHT / K 0.18 LBS

ELECTRICAL SPECIFICATION								
	MIN	MIN TOL.	NOM	MAX		FREQ.	VOLT.	
	MIN		NOM	MAX	MAX TOL.	(kHz)	(V)	URNS
L	.909	(-20%)	1.136	1.363	(+20%)	100	≤ .00037	1
Q	10		-	-		100	≤ .00037	1

COATING SPECIFICATIONS				
	TYPE	coating thickness (mils.)	Min. DLB VDC	TEST FORCE (LB)
35T0155-200	UNCOATED	-	-	-
35T0155-20P	PARYLENE	0.5	1000	.13

NOTES:



Rev	Description	Date	INT
A	Original Draft	6/9/1995	JBE
B	UPDATED TO NEW FORMAT	6/9/1995	JBE
C	TRANSFER TO LOTUS NOTES	11/19/1997	IS
D	RE-ACTIVATE PRINT REMOVE Q SPECS CHANGE P/N	10/5/2005	JRK
E	REVISED TEMPLATE	4/5/2006	WMM

Date: 4/5/06	DWG #	35T0155-20P-E	Rev:
Drawn By: WMM	Title #	35T0155-20P	E

**Steward** This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.