


NOTES:

- 1- APPLICABLE WITH FEMALE CONNECTOR 64328100X OR 64329100X
- 2- MATERIAL : >PA6.6<
- 3- APPLICATION SPECIFICATION : AS-64327-001
- 4- WEIGHT : 9.133 g

SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
	DIMENSION UNITS	SCALE	CURRENT REV DESC: MIGRATION TO NX/ECTR							 CMX 104-120CKT - WIRE CAP
mm	2:1	GENERAL TOLERANCES (UNLESS SPECIFIED)							PRODUCT CUSTOMER DRAWING	
ANGULAR TOL	± °	EC NO: 628384							DOCUMENT NUMBER	
4 PLACES ±		DRWN: GMANIVANNAN 2019/04/05							SD-64330-002	
3 PLACES ±		CHK'D: TBADAROUX 2019/12/18							DOC TYPE	
2 PLACES ±		APPR: CBOUCHAN 2019/12/20							DOC PART	
INITIAL REVISION:		DRWN: VJOUAS 2015/11/18							REVISION	
1 PLACE ±		APPR: OPLESSIS 2016/01/25							A1	
0 PLACES ±		FIRST ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		A2-SIZE		64330		643300002		CUSTOMER		
		GENERAL MARKET		SHEET NUMBER		1 OF 1				