


\* UNLESS OTHERWISE SPECIFIED TOLERANCES ON DECIMAL IS: ANGLE X.\*  $\pm$  3\* X.X\*  $\pm$  1\* UNIT: MM X.  $\pm$  0.30 X.X  $\pm$  0.25 X.XX  $\pm$  0.20 X.XXX  $\pm$  0.15

┟╎└ ╽╵┿╶┿ <del>╺┢╶</del> ┿╶┿	┥ ┥ ╋╺╋╼╋╴╋╴ ╋ <u>╺╋╺</u> ╋╶╋┨║



1. MATERIALS:

1.1 PLASTIC HOUSING: ENGINEERING THERMOPLASTIC FLAMMABILITY RATING UL 94V-0.
1.2 CONTACTS: PHOSPHOR BRONZE
1.3 PLATING: GOLD PLATING 6u" OVER NICKEL IN CONTACT.

TIN PLATING OVER NICKEL IN SOLDER AREA.

1.4 SHIELDED: BRASS WITH NICKEL PLATED

## Ordering Information

Type/Size	P/N-BULK	Product Code
2port-Shielded	2101-0112-01	MH3012-S-02

		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF MH CONNECTORS AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR	DRAWN Johnny Chen		DATE 02-08-22	
		THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	APPROVED Victor Lin		<b>DATE</b> 02-08-22	
THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2002/95/EC AND 2002/96/EC FOR RoHS COMPLIANCY.	MH CONNECTORS , DIVISION OF EDAC	SCALE	SHEET 1 OF	OF F 1	<b>REV</b> : 1.0	
		DRAWING No MH3012-S				