SIEMENS

Data sheet

US2:52BP3C2



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 12V AC/DC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Black with Red Lens 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

-	
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
material of the actuating element	metal mushroom head with plastic lens
type of unlocking device	without
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with lamp
number of lampholders	1
Display	
number of LED modules	0
General technical data	
product component	
 lamp transformer 	No
light source	Yes
degree of pollution	1
type of voltage	
 of the operating voltage 	AC/DC
 of the input voltage 	AC/DC
surge voltage resistance rated value	4 kV
protection class IP	IP66
of the terminal	IP20
operating voltage	
• at AC at 60 Hz rated value	12 13 V
• at DC rated value	12 13 V
Supply voltage	
type of voltage of the supply voltage of the light source	AC/DC
supply voltage of the light source at AC at 60 Hz	
rated value	12 V
supply voltage of the light source at DC	

rated value	12 V
Connections/ Terminals	
type of electrical connection	screw-type terminals
 of modules and accessories 	Screw-type terminal
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf·in] with screw-type terminals	8 8 lbf-in
Lamp	
type of light source	filament lamp
color of the light source	clear
Safety related data	
touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
 during operation 	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business	
Siemens is working on the renewal of the current EAC ce Please contact your local Siemens office on the status of valid EAC relevant market (other than the sanctioned EAEU memb Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/1098138 Information- and Downloadcenter (Catalogs, Brochures, https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product Cax online generator http://support.automation.siemens.com/WW/CAXorder/defaul Service&Support (Manuals, Certificates, Characteristics, https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3	dity of the EAC certification if you intend to import or offer to supply these products to an ver states Russia or Belarus). 75) ?mlfb=US2:52BP3C2 t.aspx?lang=en&mlfb=US2:52BP3C2 FAQs,)
Image database (product images, 2D dimension drawings http://www.automation.siemens.com/bilddb/cax_de.aspx?mlft	

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP3C2&lang=en

last modified:

5/31/2021 🖸