



## Main

|   |  |
|---|--|
| Product or Component Type                         | Controllers separate parts   |
| Accessory / separate part category                | Control accessory  |
| Product Specific Application                      | Light hoisting applications  |
| Product Compatibility                             | XKB  |
| Accessory / Separate Part Type                    | Contacts block   |
| Accessory / separate part specific characteristic | For use with built-in push-button handle<br>For use with Dead man's handle |

## Complementary

|   |  |
|---|--|
| Contact block per direction [control circuit] | 1 zero (center) position<br>2 zero per movement<br>4 per movement  |
| Electrical connection                         | Screw clamp terminal 1 x 0.5...1 x 1.5 mm <sup>2</sup><br>Screw clamp terminal 1 x 0.5...1 x 2.5 mm <sup>2</sup>   |
| Enclosure/cubicle description                 | Monobloc   |
| Contacts type and composition                 | 1 NO<br>2 NC<br>8 NO   |
| Contact operation                             | Double-break<br>Slow-break   |
| [Ith] conventional free air thermal current   | 10 A IEC 337-1<br>10 A NF C 63-140<br>10 A VDE 0660<br>10 A CSA C22.2 No 14  |
| [Ui] rated insulation voltage                 | 500 V AC/DC IEC 158-1<br>500 V AC/DC NF C 20-040<br>500 V AC/DC VDE 0110   |
| Maximum resistance across terminals           | 25 mOhm 1 A NF C 93-050  |
| Positive opening                              | With   |
| Short-circuit protection                      | 10 A cartridge fuse gG IEC 337-1B<br>10 A cartridge fuse gG VDE 0660 part 2  |
| Electrical durability                         | 1000000 Cycles DC inductive 120 V 75 IEC 337-1 DC-11 60 cyc/mn 0.5<br>1000000 Cycles DC inductive 24 V 90 IEC 337-1 DC-11 60 cyc/mn 0.5<br>1000000 cycles DC inductive 48 V 90 IEC 337-1 DC-11 60 cyc/mn 0.5 |
| Net Weight                                    | 0.47 lb(US) (0.215 kg)   |

## Environment

|           |                  |
|-----------|------------------|
| Standards | CENELEC EN 50013 |
|-----------|------------------|

## Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 22474 - PUSHBUTTON,CRANE JOYSTICKS |
| Discount Schedule     | I                                  |
| GTIN                  | 3389110929539                      |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 7.16 oz (203 g)                    |
| Returnability         | No                                 |
| Country of origin     | FR                                 |

## Packing Units

|                        |                   |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE               |
| Package 1 Height       | 4.06 in (10.3 cm) |
| Package 1 width        | 1.38 in (3.5 cm)  |
| Package 1 Length       | 4.06 in (10.3 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|