

SCALANCE XR524-8C; managed IE switch; layer 3 with Key-Plug available; power supply 2x 230 V AC; 24x 10/100/1000 Mbit/s RJ45; 8x 100/1000 Mbit/s SFP; contains 8 combo ports; in total 24 ports can be used; error signaling contact; select/set pushbutton; PROFINET IO device; redundancy functions; Office features (RSTP, VLAN, IGMP, ...); C-PLUG in scope of supply.



<b>product type designation</b>	<b>SCALANCE XR524-8C</b>
<b>transfer rate</b>	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
<b>interfaces / for communication / integrated</b>	
number of electrical connections	24; RJ45
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	
number of 100 Mbit/s ST(BFOC) ports	0
<ul style="list-style-type: none"> <li>for multimode</li> </ul>	
number of electrical connections	8
<ul style="list-style-type: none"> <li>for SFP</li> </ul>	
number of combo ports / with RJ45 interface for optical plug-in transceiver	8
<b>interfaces / for communication / plug-in</b>	
number of electrical connections	8
<ul style="list-style-type: none"> <li>for SFP</li> </ul>	
<b>interfaces / other</b>	
number of electrical connections	
<ul style="list-style-type: none"> <li>for operator console</li> </ul>	1
<ul style="list-style-type: none"> <li>for management purposes</li> </ul>	1
<ul style="list-style-type: none"> <li>for signaling contact</li> </ul>	1
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
type of electrical connection	
<ul style="list-style-type: none"> <li>for operator console</li> </ul>	RJ11
<ul style="list-style-type: none"> <li>for management purposes</li> </ul>	RJ45
<ul style="list-style-type: none"> <li>for signaling contact</li> </ul>	2-pole terminal block
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	4-pole terminal block
design of the removable storage	
<ul style="list-style-type: none"> <li>C-PLUG/KEY-PLUG</li> </ul>	Yes
product feature / hot-swappable interface modules	Yes
<b>signal inputs/outputs</b>	
operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> <li>at DC / rated value</li> </ul>	24 V
operational current / of the signaling contacts	
<ul style="list-style-type: none"> <li>at DC / maximum</li> </ul>	0.1 A
<b>supply voltage, current consumption, power loss</b>	
product component / connection for redundant voltage supply	Yes
type of voltage supply / redundant power supply unit	Yes
<b>type of voltage / 1 / of the supply voltage</b>	

<ul style="list-style-type: none"> <li>• supply voltage / 1 / rated value</li> </ul>	230 V
<ul style="list-style-type: none"> <li>• power loss [W] / 1 / rated value</li> </ul>	24 W
<ul style="list-style-type: none"> <li>• supply voltage / 1 / rated value</li> </ul>	90 ... 264 V
<ul style="list-style-type: none"> <li>• consumed current / 1 / maximum</li> </ul>	0.6 A
<ul style="list-style-type: none"> <li>• type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block
<ul style="list-style-type: none"> <li>• product component / 1 / fusing at power supply input</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• fuse protection type / 1 / at input for supply voltage</li> </ul>	3.15 A / 250 V
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-25 ... +60 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +85 °C
relative humidity	
<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20
<b>design, dimensions and weights</b>	
design	19" rack
number of modular height units / relating to 19-inch cabinet	1
width	449 mm
height	44 mm
depth	305 mm
net weight	4.5 kg
fastening method	
<ul style="list-style-type: none"> <li>• 19-inch installation</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• 35 mm top hat DIN rail mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• S7-300 rail mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• S7-1500 rail mounting</li> </ul>	No
type of cable outlet	Cable outlet at front
<b>product features, product functions, product components / general</b>	
cascading in cases of star topology	any (depending only on signal propagation time)
<b>product functions / management, configuration, engineering</b>	
product function	
<ul style="list-style-type: none"> <li>• CLI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• web-based management</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MIB support</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TRAPs via email</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• configuration with STEP 7</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RMON</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• port mirroring</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• multiport mirroring</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• CoS</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• PROFINET IO diagnosis</li> </ul>	Yes
PROFINET conformity class	B
product function / switch-managed	Yes
telegram length / for Ethernet / maximum	9216 byte
protocol / is supported	
<ul style="list-style-type: none"> <li>• Telnet</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTPS</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TFTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• FTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• BOOTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• GMRP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DCP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• LLDP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2</li> </ul>	Yes

<ul style="list-style-type: none"> <li>• SNMP v3</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IGMP (snooping/querier)</li> </ul>	Yes
identification & maintenance function	
<ul style="list-style-type: none"> <li>• I&amp;M0 - device-specific information</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• I&amp;M1 – higher level designation/location designation</li> </ul>	Yes

### product functions / diagnostics

product function	
<ul style="list-style-type: none"> <li>• port diagnostics</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• statistics Packet Size</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• statistics packet type</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• error statistics</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SysLog</li> </ul>	Yes

### product functions / VLAN

product function	
<ul style="list-style-type: none"> <li>• VLAN - port based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• VLAN - protocol-based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• VLAN - IP-based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• VLAN dynamic</li> </ul>	Yes
number of VLANs / maximum	255
number of VLANs - dynamic / maximum	255
protocol / is supported / GVRP	Yes

### product functions / DHCP

product function	
<ul style="list-style-type: none"> <li>• DHCP client</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP Option 82</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP Option 66</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP Option 67</li> </ul>	Yes

### product functions / routing

service / routing / note	IP routing in combination with KEY-PLUG XR-500
product function	
<ul style="list-style-type: none"> <li>• static IP routing</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• static IP routing IPv6</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• dynamic IP routing</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• dynamic IP routing IPv6</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• RIPv2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RIPnG for IPv6</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• OSPFv2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• OSPFv3 for IPv6</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• VRRP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• VRRP for IPv6</li> </ul>	Yes

### product functions / redundancy

product function	
<ul style="list-style-type: none"> <li>• ring redundancy</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• High Speed Redundancy Protocol (HRP)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• high speed redundancy protocol (HRP) with redundancy manager</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• high speed redundancy protocol (HRP) with standby redundancy</li> </ul>	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
<ul style="list-style-type: none"> <li>• media redundancy protocol (MRP) with redundancy manager</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Media Redundancy Protocol Interconnection (MRP-I)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure STP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure RSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure RSTP+</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure MSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• passive listening</li> </ul>	Yes

protocol / is supported	
<ul style="list-style-type: none"> <li>• LACP</li> </ul>	Yes
<b>product functions / security</b>	
product function	
<ul style="list-style-type: none"> <li>• ACL - MAC-based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• ACL - port/MAC-based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.1x (radius)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• broadcast/multicast/unicast limiter</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• broadcast blocking</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SSH</li> </ul>	Yes
<b>product functions / time</b>	
product function	
<ul style="list-style-type: none"> <li>• SICLOCK support</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• NTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNTP</li> </ul>	Yes
<b>standards, specifications, approvals</b>	
standard	
<ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>	in preparation
<ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>	EN 61000-6-4 (Class A)
<ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>	EN 61000-6-2
reference code	
<ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> </ul>	KF
<ul style="list-style-type: none"> <li>• according to IEC 81346-2:2019</li> </ul>	KFE
<b>standards, specifications, approvals / CE</b>	
certificate of suitability / CE marking	Yes
<b>standards, specifications, approvals / other</b>	
certificate of suitability	EN 61000-6-2, EN 61000-6-4
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• KC approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• E1 approval</li> </ul>	No
<ul style="list-style-type: none"> <li>• E1 approval</li> </ul>	No
<b>standards, specifications, approvals / marine classification</b>	
Marine classification association	
<ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• French marine classification society (BV)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DNV GL</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Korean Register of Shipping (KRS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Lloyds Register of Shipping (LRS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Nippon Kaiji Kyokai (NK)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Polski Rejestr Statkow (PRS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Royal Institution of Naval Architects (RINA)</li> </ul>	Yes
<b>further information / internet-Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>• to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>• to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>• to website: CAX-Download-Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and

---

integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

7/8/2022 