



# KBU4A thru KBU4M

Single-Phase Bridge Rectifiers  
Reverse Voltage 50 to 1000 Volts      Forward Current 4.0 Amperes

## Features


- ◆ Ideal for printed circuit boards
- ◆ High surge current capability
- ◆ High case dielectric strength of 1500 V<sub>RMS</sub>
- ◆ Solder Dip 260 °C, 40 seconds

## Mechanical Data

- ◆ Case: KBU
- Epoxy meets UL-94V-0 Flammability rating
- ◆ Terminals: Silver plated (E4 Suffix) leads, solderable per J-STD-002B and JESD22-B102D
- ◆ Polarity: As marked on body
- ◆ Mounting Torque: 10 cm-kg (8.8 inches-lbs) max.
- ◆ Recommended Torque: 5.7 cm-kg (5 inches-lbs)

## Typical Applications

General purpose use in ac-to-dc bridge full wave rectification for Monitor, TV, Printer, SMPS, Adapter, Audio equipment, and Home Appliances applications



Package outline dimensions in inches (millimeters)

## Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Parameter	Symbols	KBU4A	KBU4B	KBU4D	KBU4G	KBU4J	KBU4K	KBU4M	Units
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified output current at T <sub>C</sub> =100°C <sup>(1)</sup> T <sub>A</sub> =30°C <sup>(2)</sup>	I <sub>F(AV)</sub>				4.0	4.0			Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>				200.0				Amps
Maximum instantaneous forward voltage drop per leg at 4.0A	V <sub>F</sub>				1.0				Volt
Maximum DC reverse current at rated DC blocking voltage per leg T <sub>A</sub> =25°C T <sub>A</sub> =125°C	I <sub>R</sub>				5.0	1.0			uA mA
Typical thermal resistance per leg	R <sub>θJA</sub> R <sub>θJC</sub>				19 <sup>(2)</sup>	4.0 <sup>(1)</sup>			°C/W
Operating junction and storage temperature range	T <sub>J</sub> T <sub>STG</sub>				-55 to +150				°C

**Notes:** 1. Units mounted on a 5.1 x 5.1 x 0.15 cm thick Al. Plate

2. Units mounted on P.C.B. with 0.5 x 0.5" (13 x 13 mm) copper pads and 0.375" (9.5 mm) lead length

3. Recommended mounting position is to bolt down on heatsink with silicone thermal compound for maximum heat transfer with #6 screw

## RATINGS AND CHARACTERISTIC CURVES

( $T_A = 25^\circ\text{C}$  unless otherwise noted)




Figure 1. Derating Curve Output Rectified Current




Figure 3. Typical Forward Characteristics Per Leg




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Figure 4. Typical Reverse Leakage Characteristics Per Leg




Figure 5. Typical Junction Capacitance Per Leg