

## Economy Power

TE Internal #: 1744429-3 PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.96 mm [. 156 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Economy Power

### View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles



Connector System: Wire-to-Board

Number of Positions: 3

Number of Rows: 1

Centerline (Pitch): 3.96 mm [.156 in ]

PCB Mount Orientation: Vertical

## Features

**TE** connectivity

## Product Type Features

Connector System	Wire-to-Board				
Header Type	Partially Shrouded				
Sealable	No				
Connector & Contact Terminates To	Printed Circuit Board				
PCB Connector Assembly Type	PCB Mount Header				
Configuration Features					
Connector Contact Load Condition	Fully Loaded				
Number of Positions	3				
Number of Rows	1				
PCB Mount Orientation	Vertical				
Body Features					
Primary Product Color	Natural				
Contact Features					
Contact Mating Area Length	7.7 mm[.303 in]				

**C** For support call+1 800 522 6752

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Economy Power



Mating Square Post Dimension	1.14 mm[.045 in]	
PCB Contact Termination Area Plating Material Thickness	3 μm[120 μin]	
Contact Layout	Inline	
Contact Mating Area Plating Material Thickness	3 μm[120 μin]	
Contact Mating Area Plating Material Finish	Matte	
PCB Contact Termination Area Plating Material	Tin	
Contact Base Material	Brass	
Contact Mating Area Plating Material	Tin	
Contact Type	Pin	
Contact Current Rating (Max)	8 A	
ermination Features		
Square Termination Post & Tail Dimension	1.14 mm[.045 in]	
Termination Post & Tail Length	3.69 mm[.145 in]	
Termination Method to Printed Circuit Board	Through Hole - Solder	
lechanical Attachment		
PCB Mount Alignment Type	Boss	
Mating Alignment Type	Polarization	
Mating Retention	With	
Connector Mounting Type	Board Mount	
Mating Alignment	With	
PCB Mount Alignment	With	
PCB Mount Retention	Without	
lousing Features		
Housing Material	Nylon	
Centerline (Pitch)	3.96 mm[.156 in]	
Dimensions		
Connector Length	31.68 mm[1.247 in]	
Connector Height	9.4 mm[.37 in]	
Isage Conditions		
Operating Temperature Range	-25 – 105 °C[-13 – 221 °F]	
Operation/Application		

**C** For support call+1 800 522 6752

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Economy Power



### **Industry Standards**

Glow Wire Rating	Glow Wire			
UL Flammability Rating	UL 94V-0			
Packaging Features				
Packaging Quantity	1000			
Packaging Type	Bag			

## Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Economy Power






# Also in the Series | Economy Power



Power Contacts(8)	Rectangular Connector Housings(1)	Rectangular Power Connectors(302)	Wire-to-Board Connector Assemblies
			& Housings(142)



# Customers Also Bought



PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Economy Power





## Documents

Product Drawings 3.96 EP HDR ASSY 3P W/PEGS, GW

English

**CAD** Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1744429-3\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1744429-3\_D.3d\_igs.zip

English

Customer View Model

## ENG\_CVM\_CVM\_1744429-3\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Economy Power II (EP II) Glow Wire test compliant connectors

English

1-1773885-9 Economy Power Connectors

English

Product Specifications Application Specification

Japanese