


Power Schottky Rectifier

I_{FAV} = 6 A
V_{RRM} = 45 V
V_F = 0.5 V

V _{RSM} V	V _{RRM} V	Type DSS 6-0045AS	marking on product 6Y045AS
45	45		



TO-252 AA



A = Anode, C = Cathode , TAB = Cathode

Symbol	Conditions	Maximum Ratings		
I _{FRMS}		20	A	
I _{FAV}	T _C = 165°C; rectangular, d = 0.5	6	A	
I _{FSM}	T _{VJ} = 45°C; t _p = 10 ms (50 Hz), sine	80	A	
E _{AS}	I _{AS} = 13 A; L = 180 µH; T _{VJ} = 25°C; non repetitive	24	mJ	
I _{AR}	V _A = 1.5 • V _{RRM} typ.; f=10 kHz; repetitive	1.3	A	
(dV/dt) _{cr}		1000	V/ s	
T _{VJ}		-55...+175	°C	
T _{VJM}		175	°C	
T _{stg}		-55...+150	°C	
P _{tot}	T _C = 25°C	50	W	
Weight	typical	0.3	g	

Symbol	Conditions	Characteristic Values	
		typ.	max.
I _R ①	T _{VJ} = 25°C V _R = V _{RRM} T _{VJ} = 125°C V _R = V _{RRM}	0.3 2.5	mA mA
V _F	I _F = 6 A; T _{VJ} = 125°C I _F = 6 A; T _{VJ} = 25°C I _F = 12 A; T _{VJ} = 125 °C	0.50 0.63 0.59	V V V
R _{thJC}		3.0	K/W

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %
Data according to IEC 60747 and per diode unless otherwise specified

IXYS reserves the right to change limits, Conditions and dimensions.




Fig. 1 Maximum forward voltage drop characteristics




Fig. 2 Typ. value of reverse current I_R versus reverse voltage V_R




Fig. 3 Typ. junction capacitance C_T versus reverse voltage V_R




Fig. 4 Average forward current $I_{F(AV)}$ versus case temperature T_C




Fig. 5 Forward power loss characteristics




Fig. 6 Transient thermal impedance junction to case at various duty cycles

Note: All curves are per diode