SIEMENS

Data sheet



PE408 Port Extender for SCALANCE XM-400 managed modular IE switch; extension by 8x 10/100/1000 Mbit/s RJ45.

6GK5408-0GA00-8AP2

product type designation	SCALANCE PE408	
transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s	
interfaces / for communication / integrated		
number of electrical connections		
 for network components or terminal equipment 	8	
number of 10/100/1000 Mbit/s RJ45 ports / integrated		
 with securing collar 	8	
interfaces / other		
number of extender expansion interfaces	2	
product feature / hot-swappable interface modules	Yes	
supply voltage, current consumption, power loss		
product component / connection for redundant voltage supply	Yes	
type of voltage / 1 / of the supply voltage		
power loss [W] / 1 / rated value	4.8 W	
consumed current / 1 / maximum	0.2 A	
ambient conditions		
ambient temperature		
 during operation 	-40 +70 °C	
 during storage 	-40 +85 °C	
during transport	-40 +85 °C	
relative humidity		
 at 25 °C / without condensation / during operation / maximum 	95 %	
protection class IP	IP20	
design, dimensions and weights		
design	SIMATIC S7-1500 device design	
width	70 mm	
height	147 mm	
depth	125 mm	
net weight	0.6 kg	
fastening method		
19-inch installation	No	
 35 mm top hat DIN rail mounting 	Yes	
 wall mounting 	No	
 S7-300 rail mounting 	Yes	
S7-1500 rail mounting	Yes	
product functions / management, configuration, engineeri	product functions / management, configuration, engineering	

PROFINET conformity class	В
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
 for safety / from CSA and UL 	UL 508, UL 60950-1, CSA C22.2 Nr. 60950-1-03
for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
MTBF	58 y
reference code	
according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
standards, specifications, approvals / CE	TO E
	Vac
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environn	
standard / for hazardous zone	EN 60079-0: 2009, EN60079-15: 2010, II 3 G Ex nA IIC T4 Gc, KEMA 07 ATEX 0145 X, IECEX DEK 14.0025X
from CSA and UL	ISA 12.12.01-2012 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
certificate of suitability • CCC / for hazardous zone according to GB standard	Yes
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2, EN 61000-6-4
C-Tick	Yes
KC approval	Yes
	**
standards, specifications, approvals / marine classificatio	n
Marine classification association	
 American Bureau of Shipping Europe Ltd. (ABS) 	Yes
 French marine classification society (BV) 	Yes
 Det Norske Veritas (DNV) 	No
 Germanische Lloyd (GL) 	No
DNV GL	Yes
 Lloyds Register of Shipping (LRS) 	Yes
 Nippon Kaiji Kyokai (NK) 	Yes
 Polski Rejestr Statkow (PRS) 	Yes
Royal Institution of Naval Architects (RINA)	Yes
further information / internet-Links	
Internet-Link	
	http://www.giomono.com/tip.golootion.tool
to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
to website: Information and Download Center	http://www.siemens.com/industry/infocenter
to website: Image database	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	7/8/2022 🗗